

120V XENON STRIPS

Direct Wire and Linkable, with long-life 120V Xenon lamps

HIDE  LITE 3

FINISHES

● Bronze - 20

○ White - 30

ONE-LIGHT

P7032-20WB Bronze

P7032-30WB White

120V Xenon undercabinet.

3-1/2" W., 9-1/2" L., Extends 1-1/4".

One G8 bi-pin 120V Xenon lamp,

20w max (included).

TWO-LIGHT

P7033-20WB Bronze

P7033-30WB White

120V Xenon undercabinet.

3-1/2" W., 12" L., Extends 1-1/4".

Two G8 bi-pin 120V Xenon lamps,

each 20w max (included).

THREE-LIGHT

P7034-20WB Bronze

P7034-30WB White

120V Xenon undercabinet.

3-1/2" W., 18" L., Extends 1-1/4".

Three G8 bi-pin 120V Xenon lamps,

each 20w max (included).

FOUR-LIGHT

P7035-20WB Bronze

P7035-30WB White

120V Xenon undercabinet.

3-1/2" W., 24" L., Extends 1-1/4".

Four G8 bi-pin 120V Xenon lamps,

each 20w max (included).

*For linking cables and
junction box, see pg 770.*



P7032-20WB



P7034-20WB



P7035-20WB



P7033-20WB



P7032-30WB



P7033-30WB



P7034-30WB



P7035-30WB

Lamping

Each fixture includes 120V bi-pin 20W Xenon lamp(s) has an 8,000hr average lamp life.

Linkable

The system can be powered from a single location using the P8740 direct-wire junction box (each fixture can also be direct-wired individually). Using the HAL3 Quick-Link cables (P8733-P8743), the fixtures can be linked together to form a continuous row of illumination. (Note: The linking connections can be used with or without the use of the P8740 junction box.

Construction

Formed steel housing with a frosted tempered glass lens.

Step Dimming

Each fixture features an integral high/low/off rocker switch. Can use standard incandescent dimmer.

Mounting/Installation

Multiple 7/8" knockouts at rear of fixture. Features Quick-Link connection ports at either end for easy linking connections to other HAL3 fixtures. Slotted holes allow mounting through housing. Tool-less electrical compartment entry.