

STEPS, CORRIDORS & WALLS

BRICK LIGHTS – OUTDOOR & INDOOR



Cast aluminum housing with black aluminum louver. Three 1/2" IP conduit entries. For wood, brick, masonry, and poured concrete installations. Refer to diagram for size. UL listed for wet locations.

P6802-31 Black
IC Rated.
One 7w 2-pin twin compact fluorescent lamp, G23 base.




P6803-30 White
P6803-31 Black
Therma-Gard protection. One 25w 120V T6-1/2, intermediate base.




P6805-31 Black
One 120v 13w 2pin twin CFL GX23 base.



P6802-31 & P6803



P6821-30 & P6826-30



INDOOR & PROTECTED OUTDOOR



Spring-held white louver faceplate. Metal housing has 1/2" I.P. conduit entry. For indoor and protected outdoor use. UL listed for damp locations. Sheet rock or dry wall installations.

P6820-30TG* White
Therma-Gard protection. Porcelain socket. One 60w A19

P6820-31TG* Black
Therma-Gard protection. Porcelain socket. One 60w A19

P6821-30* White
Standard 120V NPF ballast. One 7w or 9w twin CFL lamp.



P6826-30* White
Compact fluorescent. Same as P8821-30 except with a shatter-resistant white acrylic faceplate. One 7w or 9w twin CFL lamp.



THRU-WALL DOUBLE FACE




One metal housing with two shatter-resistant white acrylic faceplates for both sides of a stud wall, 3-1/2" to 4-1/2" thick. White trim. Reduces costs by illuminating two areas with one fluorescent light. For indoor and protected outdoor use. UL listed for damp locations. Sheet rock or dry wall installations.

P6824-30* White
Compact fluorescent. One 7w or 9w twin CFL lamp.



P6825-30* White
Same as P6824-30 except with two louver faceplates. One 7w or 9w twin CFL lamp.



INDOOR & OUTDOOR



P6816-16



P6817-16



P6817-31

Cast aluminum, tempered glass with louver faceplate. Two 1/2" I.P. for conduit entry. For poured concrete and masonry installations. UL listed for wet locations. Refer to diagram for size.


P6818-16 Satin Aluminum
White glass face. One medium base, 75w max.

P6817-16 Satin Aluminum
Louver faceplate over glass. One medium base, 25w max.


P6817-31 Black
Louver faceplate over glass. One medium base, 25w max.

P6816-16 Satin Aluminum
White glass face. One medium base, 25w max.

P6816-16 & P6817-16,31



P6818-16 & P6819-16



LED STEP & WALL LIGHTS

5w 3000K color temperature with 84+ CRI and a 120° beam spread. LED step/wall lights are available in a vertical or horizontal configuration for mounting into a single-gang wallbox.

- cCSAus listed for wet locations
- Integral power supply module in a compact package
- Consumes less than 5w of power per fixture
- Warm white 3000K LED's included
- 84+ CRI
- Beam spread: 120 degrees



P6827-0930K



P6827-2030K



P6828-0930K



P6828-3030K



P6827-3030K



P6827-3130K



P6828-2030K



P6828-3130K

PRODUCT NO.	FINISH	DESCRIPTION	SIZE	LAMP
P6827-0930K	Brushed Nickel	Louvered horizontal step/wall light	5-1/4" W. 3-1/2" ht.	5w LED module included 102 lumens
P6827-2030K	Antique Bronze			
P6827-3030K	White			
P6827-3130K	Black			
P6828-0930K	Brushed Nickel	Louvered vertical step/wall light	3-1/2" W. 5-1/4" ht.	5w LED module included 108 lumens
P6828-2030K	Antique Bronze			
P6828-3030K	White			
P6828-3130K	Black			

P6829 and P6832 LED step/wall lights provide an attractive solution for a variety of illumination tasks

- cCSAus listed for outdoor as well as indoor applications
- Integral power supply module in a compact package
- Consumes less than 4w of power per fixture
- Warm white 3000K LED's included
- 84+ CRI
- Beam spread: 120 degrees



P6829-0930K



P6829-2030K



P6829-3030K



P6829-3130K

U.S. Patent #. 6357891, 5379199

PRODUCT NO.	FINISH	DESCRIPTION	SIZE	LAMP
P6829-0930K	Brushed Nickel	Vertical step/wall light	2-3/4" W. 4-1/2" ht.	5w LED module included 84 lumens
P6829-2030K	Antique Bronze			
P6829-3030K	White			
P6829-3130K	Black			



P6832-0930K



P6832-2030K

PRODUCT NO.	FINISH	DESCRIPTION	SIZE	LAMP
P6832-0930K	Brushed Nickel	Horizontal step/wall light	2-7/8" W. 4-1/2" ht.	5w LED module included 65 lumens
P6832-2030K	Antique Bronze			
P6832-3030K	White			
P6832-3130K	Black			



P6832-3030K



P6832-3130K