

6" SLOPED CEILING

HOUSINGS & TRIMS

For complete fixture, order housing with trim.

6" 45° IC Sloped Ceiling Housing

New Construction IC



P645-TG

Ceiling opening: 6-7/8"
Plaster frame: 8-3/8" x 13"
Recessed depth: 7-5/8"
Pryouts: 1/2" & 3/4"

P645-TG

- Maintains lamp in a vertical position from a 0° to a 45° slope (0/12 to 12/12 pitch)
- Easy spring installation of trims
- Bar hangers, with nail grip feature, span to position housing anywhere within 24" joist spacing
- Locking screw to secure housing in place
- Rated for 8 #12 90° conductors (4 in/4 out)
- Integral Romex clamps
- Integral nailer and T-bar clamps
- UL and CUL listed for damp locations and through wiring
- Can be installed in ceiling from 1/2" to 1-1/2"

New Construction Air-Tight & IC



P645-AT

Ceiling opening: 6-7/8"
Plaster frame: 8-3/8" x 13"
Recessed depth: 7-5/8"
Pryouts: 1/2" & 3/4"

P645-AT

- Maintains lamp in a vertical position from a 0° to a 45° slope (0/12 to 12/12 pitch)
- Meets Washington State Energy Code requirements
- Bar hangers, with nail grip feature, span to position housing anywhere within 24" joist spacing
- Locking screw to secure housing in place
- Rated for 8 #12 90° conductors (4 in/4 out)
- Integral Romex clamps
- Integral nailer and T-bar clamps
- UL and CUL listed for damp locations and through wiring
- Can be installed in ceiling from 1/2" to 1-1/2"

6" 45° Remodel Sloped Ceiling Housing

Remodel IC



P745-IC

Ceiling opening: 7-3/8"
Recessed depth: 7-1/4"
Pryouts: 1/2"

P745-IC

- Maintains lamp in a vertical position from a 0° to a 45° slope (0/12 to 12/12 pitch)
- Easy spring installation of trims
- Bar hangers, with nail grip feature, span to position housing anywhere within 24" joist spacing
- Slide bars stay in place, and have locking screw to secure housing in place
- Rated for 4 #12 90° conductors (2 in/2 out)
- Integral Romex clamps
- Integral nailer and T-bar clamps
- UL and CUL listed for damp locations and through wiring
- Can be installed in ceiling from 1/2" to 1-1/4"

TRIMS

8-1/4" outside diameter

BAFFLES

P8004-20 Antique Bronze

P8004-28 White

P8004-31 Black



P8004-20



P8004-28



P8004-31

Lamps

CATALOG NO. LAMP(S)

P645-TG 75w BR 30, 75w BR30/PAR 30LN

P645-AT 75w BR 30, 75w PAR 30LN

P745-IC 65w BR 30, 75w PAR 30LN

Lamp wattages shown are maximum.