

4" LOW VOLTAGE MR 16

HOUSINGS & TRIMS

For complete fixture, order housing with trim.

Low Voltage Housing

New Construction Air-Tight & IC



P817-AT

Ceiling opening: 4-1/2"
Plaster frame: 15-3/4" x 9-3/4"
Recessed depth: 7-1/2"
Pryouts: 1/2" & 3/4"

P817-AT

- UL and CUL Listed for damp locations and through wiring
- Meets Washington State Energy Code requirements
- Electronic transformer
- Can be installed in ceilings from 1/2" to 2-1/2" thick
- Rated for 8 #12 90° conductors (4 in/4 out)

New Construction Non-IC



P816-TG

Ceiling opening: 4-1/2"
Plaster frame: 7-7/8" x 10-3/4"
Recessed depth: 5-1/2"
Pryouts: 1/2" & 3/4"

P816-TG

- UL and CUL Listed for damp locations and through wiring
- Rated for 8 #12 90° conductors (4 in/4 out)
- Can be installed in ceilings from 1/2" to 2-1/2" thick
- Magnetic transformer

Remodel Non-IC



P818-TG

Ceiling opening: 4-1/4"
Recessed depth: 5-1/2"
Pryouts: 1/2"

P818-TG

- Integral flange on housing and exclusive locking bars permit quick mounting on ceilings from 1/2" to 1" thick
- UL & CUL Listed for damp locations
- Rated for 4 #12 90° conductors (2 in/2 out)
- Rated for 60° supply wires in end-of-run applications
- Magnetic transformer

IC Trims & Non-IC Trims

5" outside diameter All trims have 360° positioning Lamps tilt 30° max.



STEP BAFFLE

P8037-28 White Baffle
12V 50w MR-16



STEP BAFFLE

P8037-31 Black Baffle
12V 50w MR-16



STEP BAFFLE

P8037-09 Brushed Nickel
12V 50w MR-16



SLOTTED

P8039-28 White
12V 35w MR-16
12V 50w MR-16



PINHOLE

P8036-28 White
12V 35w MR-16
12V 50w MR-16



WALL WASHER

P8045-31 White with
Black Baffle
12V 35w MR-16
12V 50w MR-16



EYEBALL

P8057-28 White
Rotates 360°, tilts 30°
12V 50w MR-16



EYEBALL

P8057-20 Antique Bronze
12V 50w MR-16



ALZAK® CONE

P8056-21 Clear Alzak®
12V 50w MR-16

Lamp wattages shown are maximum.