


4" PRO-OPTIC®

4" New Construction Housing

CEILING OPENING	CEILING THICKNESS	PRYOUTS	PRODUCT NO.	DESCRIPTION
5-3/8"	1-1/4"	1/2" and 3/4"	P8064-EBG4	4" New Construction Housing



P8064-EBG4

1100 Lumen Open Module Trims

P8067-21A/30KG4	P8067-22A/30KG4	P8067-28/30KG4
P8067-21A/35KG4	P8067-22A/35KG4	P8067-28/35KG4
P8067-21A/40KG4	P8067-22A/40KG4	P8067-28/40KG4
Clear Alzak®	Gold Alzak®	White



LED FEATURES

- Universal 120 - 277V high efficiency driver
- Remote phosphor technology for controlled color consistency
- 3000K, 3500K and 4000K options
- 80+ CRI
- 50 lumens per watt fixture efficacy
- TM-21 50,000 hour life
- J-box rated for (8) #12 90° conductors (4 in/4 out)

2000 Lumen Open Module Trims

P8206-21A/30KG4	P8206-22A/30KG4	P8206-28/30KG4
P8206-21A/35KG4	P8206-22A/35KG4	P8206-28/35KG4
P8206-21A/40KG4	P8206-22A/40KG4	P8206-28/40KG4
Clear Alzak®	Gold Alzak®	White



- Light commercial bar hangers included
- Suitable for wet locations, non-IC rated
- 5 year warranty

6" PRO-OPTIC®

6" New Construction Housing

CEILING OPENING	CEILING THICKNESS	PRYOUTS	PRODUCT NO.	DESCRIPTION
6-1/4"	1-1/4"	1/2" and 3/4"	P8216-EB P8216-DM P8216-277EB P8216-277DM	Built to order with a 2-4 week lead time



900 Lumen Open Module Trims

P8104-2830K
P8104-2835K
P8104-2840K
White



LED FEATURES

- 120V or 277V high efficiency driver
- Remote phosphor technology for controlled color consistency
- 3000K, 3500K and 4000K options
- 80+ CRI
- 50 lumens per watt fixture efficacy
- TM-21 50,000 hour life
- J-box rated for (8) #12 90° conductors (4 in/4 out)
- Light commercial bar hangers incl.

1300 Lumen Open Module Trims

P8105-2830K
P8105-2835K
P8105-2840K
White



1500 Lumen Open Module Trims

P8106-2830K
P8106-2835K
P8106-2840K
White



6" PRO-OPTIC®

CEILING OPENING	CEILING THICKNESS	PRYOUTS	PRODUCT NO.	DESCRIPTION
6-1/4"	1-1/4"	1/2" and 3/4"	P8023-EBG4	New Construction
Min. 5-16/16". Max. 6-1/8".	1-1/2"	1/2" and 3/4"	P8002-EBG4	Retrofit
Min. 5-16/16". Max. 6-1/8".	1-1/2"	1/2" and 3/4"	P8002-EBSDG4	Small Diameter Retrofit



LED FEATURES

- 120V or 277V high efficiency driver
- Remote phosphor technology for controlled color consistency
- 3000K, 3500K and 4000K options
- 80+ CRI
- 50 lumens per watt fixture efficacy
- TM-21 50,000 hour life
- J-box rated for (8) #12 90° conductors (4 in/4 out)
- Light commercial bar hangers incl.
- Suitable for wet locations, non-IC rated
- 5 year warranty

1100 Lumen Open Module Trims

P8021-21A/30KG4	P8021-22A/30KG4	P8021-28/30KG4
P8021-21A/35KG4	P8021-22A/35KG4	P8021-28/35KG4
P8021-21A/40KG4	P8021-22A/40KG4	P8021-28/30KG4
Clear Alzak®	Gold Alzak®	White



1100 Lumen Open Module Trims - Wide Flange

P8021-21A/30KWFG4	P8021-22A/30KWFG4	P8021-28/30KWFG4
P8021-21A/35KWFG4	P8021-22A/35KWFG4	P8021-21A/35KWFG4
P8021-21A/35KWFG4	P8021-22A/35KWFG4	P8021-21A/35KWFG4
Clear Alzak®	Gold Alzak®	White



2000 Lumen Open Module Trims

P8050-21A/30KG4	P8050-22A/30KG4	P8050-28/30KG4
P8050-21A/35KG4	P8050-22A/35KG4	P8050-28/35KG4
P8050-21A/40KG4	P8050-22A/40KG4	P8050-28/40KG4
Clear Alzak®	Gold Alzak®	White



2000 Lumen Open Module Trims - Wide Flange

P8050-21A/30KWFG4	P8050-22A/30KWFG4	P8050-28/30KWFG4
P8050-21A/35KWFG4	P8050-22A/35KWFG4	P8050-28/35KWFG4
P8050-21A/40KWFG4	P8050-22A/40KWFG4	P8050-28/40KWFG4
Clear Alzak®	Gold Alzak®	White



6" PRO-OPTIC® - HIGH LUMEN

CEILING OPENING	CEILING THICKNESS	PRYOUTS	PRODUCT NO.	DESCRIPTION
6-1/4"	1-1/4"	1/2" and 3/4"	P8212-EB120VG4	New Construction 120V
Min. 5-16/16". Max. 6-1/8".	1-1/2"	1/2" and 3/4"	P8212-EB277VG4	New Construction 277V
Min. 5-16/16". Max. 6-1/8".	1-1/2"	1/2" and 3/4"	P8214-EB120VG4	Retrofit 120V
			P8214-EB277VG4	Retrofit 277V
			P8214-EBSD120VG4	Retrofit 120V
			P8214-EBSD277VG4	Retrofit 277V



LED FEATURES

- 120V or 277V high efficiency driver
- Remote phosphor technology for controlled color consistency
- 3000K, 3500K and 4000K options
- 80+ CRI
- 50 lumens per watt fixture efficacy
- TM-21 50,000 hour life
- J-box rated for (8) #12 90° conductors (4 in/4 out)
- Light commercial bar hangers incl.
- Suitable for wet locations, non-IC rated
- 5 year warranty

2800 Lumen Open Module Trims

P8112-21A/30KG4	P8112-22A/30KG4	P8112-28/30KG4
P8112-21A/35KG4	P8112-22A/35KG4	P8112-28/35KG4
P8112-21A/40KG4	P8112-22A/40KG4	P8112-28/40KG4
Clear Alzak®	Gold Alzak®	White



2800 Lumen Open Module Trims - Wide Flange

P8112-21A/30KWFG4	P8112-22A/30KWFG4	P8112-28/30KWFG4
P8112-21A/35KWFG4	P8112-22A/35KWFG4	P8112-28/35KWFG4
P8112-21A/40KWFG4	P8112-22A/40KWFG4	P8112-28/40KWFG4
Clear Alzak®	Gold Alzak®	White



6" PRO-OPTIC® - WALL WASH

CEILING OPENING	CEILING THICKNESS	PRYOUTS	PRODUCT NO.	DESCRIPTION
6-1/4"	1-1/4"	1/2" and 3/4"	P8005-EBG4	New Construction Wall Wash 110 & 2000 Lumens
LED FEATURES 120V or 277V high efficiency driver - Remote phosphor technology for controlled color consistency 3000K, 3500K and 4000K options 80+ CRI 50 lumens per watt fixture efficacy - TM-21 50,000 hour life - J-box rated for (8) #12 90° conductors (4 in/4 out) - Light commercial bar hangers incl. - Suitable for damp locations, non-IC rated 5 year warranty				



1100 Lumen Open Module Trims

P8006-21A/30KG4
P8006-21A/35KG4
P8006-21A/40KG4
Clear Alzak®



P8006-22A/30KG4
P8006-22A/35KG4
P8006-22A/40KG4
Gold Alzak®



2000 Lumen Open Module Trims

P8051-21A/30KG4
P8051-21A/35KG4
P8051-21A/40KG4
Clear Alzak®



P8051-22A/30KG4
P8051-22A/35KG4
P8051-22A/40KG4
Gold Alzak®



6" PRO-OPTIC® - HIGH LUMEN WALL WASH

CEILING OPENING	CEILING THICKNESS	PRYOUTS	PRODUCT NO.	DESCRIPTION
6-1/4"	1-1/4"	1/2" and 3/4"	P8223-EB120VG4 P8223-EB277VG4	New Construction 120V New Construction 277V Wall Wash
LED FEATURES 120V or 277V high efficiency driver - Remote phosphor technology for controlled color consistency 3000K, 3500K and 4000K options 80+ CRI 50 lumens per watt fixture efficacy - TM-21 50,000 hour life - J-box rated for (8) #12 90° conductors (4 in/4 out) - Light commercial bar hangers incl. - Suitable for damp locations, non-IC rated 5 year warranty				



2800 Lumen Open Module Trims

P8123-21A/30KG4
P8123-21A/35KG4
P8123-21A/40KG4
Clear Alzak®



P8123-22A/30KG4
P8123-22A/35KG4
P8123-22A/40KG4
Gold Alzak®



P8123-28/30KG4
P8123-28/35KG4
P8123-28/40KG4
White



8" PRO-OPTIC®

8" New Construction and Retrofit Housing

PLASTER FRAME	CEILING THICKNESS	PRYOUTS	PRODUCT NO.	CEILING OPENING
9"x13-3/4" to 16"	1-1/4"	1/2" and 3/4"	P8102-EBG4	Min. 8-1/8". Max. 8-3/4".
9"x13-3/4" to 16"	1-1/4"	1/2" and 3/4"	P8102-EBSDG4	Min. 7-5/16". Max. 8-1/8".
9"x15-1/2"	1-1/4"	1/2" and 3/4"	P8103-EBG4	8" New Construction



LED FEATURES

- 120V or 277V high efficiency driver
 - Remote phosphor technology for controlled color consistency
 - 3000K, 3500K and 4000K options
 - 80+ CRI
- 50 lumens per watt fixture efficacy
 - TM-21 50,000 hour life
 - J-box rated for (8) #12 90° conductors (4 in/4 out)
 - Light commercial bar hangers incl.
- Suitable for wet locations, non-IC rated
 - 5 year warranty



1100 Lumen Open Module Trims - EB

P8121-21A/30KG4
P8121-21A/35KG4
P8121-21A/40KG4
Clear Alzak®



P8121-22A/30KG4
P8121-22A/35KG4
P8121-22A/40KG4
Gold Alzak®



P8121-28/30KG4
P8121-28/35KG4
P8121-28/40KG4
White



1100 Lumen Open Module Trims - EBSD

P8121-21A/30KWFG4
P8121-21A/35KWFG4
P8121-21A/40KWFG4
Clear Alzak®



P8121-22A/30KWFG4
P8121-22A/35KWFG4
P8121-22A/40KWFG4
Gold Alzak®



P8121-28/30KWFG4
P8121-28/35KWFG4
P8121-28/40KWFG4
White



2000 Lumen Open Module Trims - EB

P8133-21A/30KG4
P8133-21A/35KG4
P8133-21A/40KG4
Clear Alzak®



P8133-22A/30KG4
P8133-22A/35KG4
P8133-22A/40KG4
Gold Alzak®



P8133-28/30KG4
P8133-28/35KG4
P8133-28/40KG4
White



2000 Lumen Open Module Trims - EBSD

P8133-21A/30KWFG4
P8133-21A/35KWFG4
P8133-21A/40KWFG4
Clear Alzak®



P8133-22A/30KWFG4
P8133-22A/35KWFG4
P8133-22A/40KWFG4
Gold Alzak®



P8133-28/30KWFG4
P8133-28/35KWFG4
P8133-28/40KWFG4
White



8" PRO-OPTIC®

8" New Construction and Retrofit Housing - High Lumen

PLASTER FRAME	CEILING THICKNESS	PRYOUTS	PRODUCT NO.	CEILING OPENING
9"x13-3/4" to 16"	1-1/4"	1/2" and 3/4"	P8215-EB120VG4 P8215-EB277VG4	Min. 8-1/8". Max. 8-3/4".
			P8215-EBSD120VG4 P8215-EBSD277VG4	Min. 7-5/16". Max. 8-1/8".
			P8220-EB120VG4 P8220-EB277VG4	8" New Construction



LED FEATURES

- 120V or 277V high efficiency driver
- Remote phosphor technology for controlled color consistency
- 3000K, 3500K and 4000K options
- 80+ CRI
- 50 lumens per watt fixture efficacy
- TM-21 50,000 hour life
- J-box rated for (8) #12 90° conductors (4 in/4 out)
- Light commercial bar hangers incl.
- Suitable for wet locations, non-IC rated
- 5 year warranty



3000 Lumen Open Module Trims - EB

P8120-21A/30KG4	P8120-22A/30KG4	P8120-28/30KG4
P8120-21A/35KG4	P8120-22A/35KG4	P8120-28/35KG4
P8120-21A/40KG4	P8120-22A/40KG4	P8120-28/40KG4
Clear Alzak®	Gold Alzak®	White



3000 Lumen Open Module Trims - EBSD

P8120-21A/30KWFG4	P8120-22A/30KWFG4	P8120-28/30KWFG4
P8120-21A/35KWFG4	P8120-22A/35KWFG4	P8120-28/35KWFG4
P8120-21A/40KWFG4	P8120-22A/40KWFG4	P8120-28/40KWFG4
Clear Alzak®	Gold Alzak®	White



Featuring 8" Pro-Optic®