

8" SLOPED CEILING

HOUSINGS & TRIMS

For complete fixture, order housing with trim.

8" 45° Remodel Sloped Ceiling Housings

Remodel IC



P245-TG

Ceiling opening: 8"
Recessed depth: 7-13/16"
Pryouts: 1/2"

P245-TG

- UL and CUL listed for damp locations and through wiring
- Single spring installation of trims
- Lamp is adjustable to vertical position in 9° to 45° ceilings (2/12 to 12/12 pitch)
- Rated for 4 #12 90° conductors (2 in/2 out)
- Rated for 60° supply wires in end of run applications
- Exclusive mounting bars permit quick and solid mounting
- Cast trim flange is integral part of housing
- Can be installed in ceilings from 1/2" to 1-1/2" thickness

8" 45° Sloped Ceiling Housing

New Construction Air-Tight & IC



P45-AT

Ceiling opening: 8-3/4"
Plaster frame: 15-3/4" x 9-3/4"
Recessed depth: 7-1/2"
Pryouts: 1/2" & 3/4"

P45-AT

- Maintains lamp in a vertical position in 9° to 45° ceilings (2/12 to 12/12 pitch)
- Single spring installation of trims
- Meets Washington State Energy Code requirements
- Integral nailer and T-bar mounting clamp
- UL & CUL listed for damp locations and through wiring
- Can be installed in ceilings from 1/2" to 1-1/2" thick

TRIMS

9-3/4" outside diameter

BAFFLES

P8000-28 White
P8000-31 Black

ALZAK® CONES

P8001-21 Clear Alzak®
P8001-22 Gold Alzak®



P8000-28



P8000-31



P8001-21



P8001-22

Lamps

CATALOG NO. LAMP(S)

P45-AT 120w PAR 38, BR40
P245-TG 75w PAR 38, BR40