


RECESSED ACCESSORIES

P8588-01 4" ceiling gasket
P8584-01 5" ceiling gasket
P8587-01 6" ceiling gasket
P8589-01 8" ceiling gasket
Ceiling gasket seals housing to drywall opening for Washington State Energy Code compliance.



P8584-01
P8588-01
P8587-01
P8589-01

P8773-01
Four mounting clips and screws for T-Bar ceilings for any new construction recessed product using bar hangers.



P8773-01

P8585-01 Goof Ring
8-7/8".
For use with any recessed trim with a 7-3/4" OD.




P8585-01

P8700-01
Four plaster frame clips and screws for complete squares and rounds.



P8700-01

P8607-01 Remodel Clips
Three plaster frame clips for use in new construction frames in finished ceilings.




P8607-01

P8511-01
Furring channel mounting clip for bar hangers.



P8511-01

P8716-01 Adjustable hangers
Two 26" adjustable hangers for step lights, complete rounds and squares.



P8716-01

P8593-01
Airtight Gasket Kit to convert the P86-TG, P186-TG P183-26EB to an air tight unit. When not using caulk at the ceiling line, P8587-01 may also be required.



P8593-01

RECESSED ENCLOSURE FOR NON-IC HOUSINGS IN IC APPLICATIONS




- Material is Coroplast™, which is made from polypropylene co-polymer resin
- Deflection temperature F(@66psi) = 194 (90°C)
- Melting point = 162°C, 324°F
- Normal temperature performance range = -17°F to 160°F
- MSDS available upon request

APPLICATION

- Use to create a barrier to keep insulation from making contact with the following type Non-IC rated recessed housings: P60-FB, P62-FB, P821-FB, P821-FBFC, P85-FB, P831-FB, P85-TG, P830-TG, P86-TG, P816-TG
- Requires no insulation on top

U.S. Patent #: 6,872,885

P8555-01 IC Barrier
Creates a barrier to prevent insulation from making contact with recessed fixtures. For use only with Firebox, Pro-Optic, P816, P830, P85-TG, and P83. For use with any other Progress fixture consult factory.



P8555-01 IC Box flat

Note: The P8555-01 does not make recessed housings IC-rated.

Dimensions: 24-1/2"W. x 35"Ht.

EMERGENCY BATTERY PACK



Emergency battery packs for remote mounting. Can be used with any compact fluorescent fixture. Remote battery must be located within 50 feet of ballast, or 1/2 the recommended distance specified by the AC Ballast manufacturer, whichever is less. Comes with test switch, indicator light, junction box and 4ft of flex.

PRODUCT NO.	WATTS	LAMP	LENGTH	WIDTH	HEIGHT
P8643-01	10-42W	4 pin Quad, Triple, 2D and twins	9-1/2"	2-3/8"	1-1/2"

BAR HANGARS

P8725-01
Bar Hangar for T-Bar.

P8739-01
Bar Hangar for joist.

SPECIALTY RECESSED HOUSINGS & TRIMS



P6917-TG

COMPLETE ROUND

Unwired unit: White trim, housing, plaster frame, clips and 4-1/2 feet of wire. All are UL listed for damp locations. Therma-Gard™ automatic resetting thermal protection. Needs P8700-01 or P8716-01 mounting hardware for installation.

Cat. No.	P6917-TG
Desc.	Open trim, unwired
Finish	White
Plaster Frame	6-5/8" sq.
Recess Depth	5-3/4"
Ceiling Opening	4-1/2"
Trim O.D.	5-7/8"
Lamp	45w BR 30, 50w PAR 30



P6952-16TG

BATH

Complete with housing, trim and 26" adjustable bar hangers. Therma-Gard™ automatic resetting thermal protection. Junction box has riveted ground, 9 K.O.'s. UL listed for damp locations. Thru-branch wiring, 4 in, 4 out.

Cat. No.	P6952-16TG
Desc.	Heater light
Finish	Satin aluminum
Plaster Frame	8-3/8" x 13"
Recess Depth	7-3/4"
Ceiling Opening	6-7/8"
Trim O.D.	7-3/4"
Lamp	250w R 40



P6414-30TG
P6416-30TG

COMPLETE SQUARE

Complete with housing and trim. Flat white glass. Torsion springs for easy relamping. UL listed for damp locations. Therma-Gard™ automatic resetting thermal protection. Needs P8700-01 or P8716-01 mounting hardware for installation.

Cat. No.	P6414-30TG	P6416-30TG
Desc.	Pre-wired	White
Finish	Pre-wired	White
Recess Depth	4-1/4"	4-1/4"
Ceiling Opening	8-1/8"	10-1/8"
Trim (Sq.)	9-1/2"	11-1/2"
Lamp	100w	150w

INSTALLATION HARDWARE FOR P6917, P6414 AND P6416

P8700-01 Four clips for finished or suspended ceiling installation.
P8716-01 accessory bar hangers for new construction.
For use with complete squares (P6414, P6416) and complete rounds (P6917).