

5" INCANDESCENT FIRE RATED

HOUSING

New Construction Fire Rated Ceilings



P85-FB

- Non-IC rated*
- Fits into 2" x 10" construction
- UL Classified to maintain fire rating of 1 hour or less for UL P500 series roof/ceiling designs
- UL Classified to maintain fire ratings of 2 hours or less for UL D200, D500, G200, G500, L200 and L500 series floor/ceiling designs



P85-FB

Ceiling Opening: 5-1/4"

Recessed Depth: 9-1/16"

Plaster Frame: 9-9/16" x 13-1/4"

Pryouts: 1/2" & 3/4"

**IC Box to allow
use in IC rated applications.*

U.S. Patent #:
5758959, 6004011,
6357891, 6254527

TRIMS FOR P85-FB

6-1/8" outside diameter, except where indicated.



EYEBALL

P8176-28 White
75w PAR 30SN



STEP BAFFLE

P8175-20 Antique Bronze
P8175-31 Black
65w BR 30, 50w PAR 30



STEP BAFFLE

P8175-28 White
65w BR 30, 50w PAR 30



OPEN

P8168-28 White
65w BR 30,
50w PAR 30 LN



DEEP CONE

P8172-09 Brushed Nickel
85w BR 30,
50w PAR 30 Short Neck



ALZAK®

P8172-22A Gold Alzak®
P8172-21A Clear Alzak®
85w BR 30,
50w PAR 30 Short Neck



OPEN SHOWER

P8367WL-28 White
Wet Location listed
50w PAR 30*



SHOWER LIGHT

P8109-60 White Glass
Wet Location listed
Metal flange
40w A19, 50w PAR30
Short Neck

** WL trims require use with
outdoor rated PAR lamps*

