

Project:	
ixture Type:	
ocation:	
Contact:	

One-Light LED Flush Mount

Ceiling mounted • Damp location listed PROGRESS LED



Description:

One-light 19 inch LED Flush Mount in Antiques Bronze features an etched Alabaster glass bowl. Fixtures are dimmable to 10 percent with Triac, phase forward or ELV dimmers. 3000K and 90 CRI.

Specifications:

- · Antique Bronze (-020) (painted)
- Steel Construction
- Etched Alabaster glass bowl
- 1838 lumens 62 lumens/watt (delivered)
- · 3000K color temperature, 90+ CRI
- · TM-21 54,000 hour life.
- · Dimmable to 10% brightness (See Dimming Notes)
- Unit covers a standard 4" octagonal recessed outlet box
- · Mounting strap for outlet box included
- 6" of wire supplied
- · ENERGY STAR® qualified
- · Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	30w
Input Voltage	120 V
Input Frequency	50/60 Hz
Lumens/LPW (Source)	2622/88 (LM-82)
Lumens/LPW (Delivered)	1838/62 (LM-79)
ССТ	3000 K
CRI	90+
Life (hours)	54,000 (L70/TM-21)
FCC	FCC Title 47, Part 15, Class B
Min. Start Temp	-25 °C
Max. Operating Temp	25 °C
Warranty	5 year warranty
Labels	ETL Damp location listed
	ENERGY STAR® qualified
	Meets California Title 24 JA8-2016



Images:



Dimensions:

Diameter: 19" Height: 8-3/4"





One-Light LED Flush Mount

Ceiling mounted • Damp location listed PROGRESS LED



P350004-020-30

Dimming Notes:

P350004 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron NTELV-300 Leviton 6681 Leviton 6672 Leviton 6674 Lutron AYCL-153P Lutron AYLV-600P Lutron NTLV-600 Lutron MAELV-601 Leviton AWRMG-EAW Lutron N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.