



## EMT

### Steel Compression Couplings

#### Features

- Heavy steel walls
- Concrete tight
- UL Listed for Steel & Aluminum EMT Conduit
- RoHS compliant

#### Standard Materials


Steel

#### Standard Finish

Zinc plated

#### Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. W-F-408E
- NEMA: FB-1
- UL Listed File # E200730



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	INNER PACK	MASTER PACK	WEIGHT PER C
CK50RKON	1/2"	1.625	1.125	50	500	14.0
CK75RKON	3/4"	1.750	1.375	25	250	21.3
CK100RKON	1"	1.875	1.688	20	200	28.0
CK125RKON	1-1/4"	2.250	2.063	10	100	48.5
CK150RKON	1-1/2"	2.250	2.250	10	100	59.5
CK200RKON	2"	2.375	2.750	5	50	78.9
CK250RKON	2-1/2"	3.875	3.625	–	8	205.5
CK300RKON	3"	4.000	4.250	–	6	263.0
CK350RKON	3-1/2"	4.063	4.688	–	4	309.4
CK400RKON	4"	4.938	5.188	–	4	393.4