

Galvanized Rigid Special Radius 90° Sweeps

Application:

Galvanized Rigid Conduit (GRC) Elbows are to be installed on conduit raceways for underground stub-ups, and interconnection of conduit runs and other fittings.

Features:


Fabricated from UL listed hot-dipped galvanized rigid conduit
Threaded ends (NPT)

Certifications and Compliances:

- UL & CUL Listed - UL6
- UL File Number E226472
- UL6 with statements of conformance
- ANSI C80.1
- CalTrans Specification 86-2.05
- A.R.R.A. Available
- ASTM A239

Options:

Available in any degree of bend from 5° to 90°, and special radius



*All dimensions are for informational purposes only
Tolerances +/-5%

12" - 18"								
Radius								
A	12 Inch				18 Inch			
Size	Item Number	B	T	Wt.	Item No	B	T	Wt.
½"	ST0512SW90	21	10	2.60	ST0518SW90	28	11	3.60
¾"	ST0712SW90	21	10	3.50	ST0718SW90	28	11	4.70
1"	ST1012SW90	21	10	5.00	ST1018SW90	28	11	6.00
1-¼"	ST1212SW90	21	10	6.00	ST1218SW90	28	11	9.00
1-½"	ST1512SW90	21	10	8.00	ST1518SW90	28	11	11.40
2"					ST2018SW90	28	11	15.20
2-½"					ST2518SW90	28	11	24.30
3"					ST3018SW90	28	11	32.90
3-½"					ST3518SW90	28	11	39.00

Calconduit™

Rigid Conduit, Rigid & EMT Fittings

Galvanized Rigid Special Radius 90° Sweeps

All dimensions are for informational purposes only

*Tolerances +/-5%

24" - 30" - 36"												
Radius												
A	24 Inch				30 Inch				36 Inch			
Size	Item Number	B	T	Wt.	Item No	B	T	Wt.	Item No	B	T	Wt.
½"	ST0524SW90	35	11	4.10	ST0530SW90	41	11	4.90	ST0536SW90	47	11	5.50
¾"	ST0724SW90	35	11	5.50	ST0730SW90	41	11	6.50	ST0736SW90	47	11	7.30
1"	ST1024SW90	35	11	8.00	ST1030SW90	41	11	9.00	ST1036SW90	47	11	10.00
1-¼"	ST1224SW90	35	11	11.00	ST1230SW90	41	11	12.00	ST1236SW90	47	11	14.00
1-½"	ST1524SW90	35	11	13.20	ST1530SW90	41	11	15.80	ST1536SW90	47	11	17.50
2"	ST2024SW90	35	11	17.50	ST2030SW90	41	11	21.00	ST2036SW90	47	11	23.30
2-½"	ST2524SW90	35	11	28.00	ST2530SW90	41	11	33.60	ST2536SW90	47	11	37.30
3"	ST3024SW90	35	11	38.00	ST3030SW90	41	11	45.60	ST3036SW90	47	11	50.70
3-½"	ST3524SW90	35	11	45.00	ST3530SW90	41	11	54.00	ST3536SW90	47	11	60.00
4"	ST4024SW90	35	11	52.50	ST4030SW90	41	11	63.00	ST4036SW90	47	11	70.00
5"									ST5036SW90	47	11	93.30
6"									ST6036SW90	48	12	123.30

42" - 48" - 60"												
Radius												
A	42 Inch				48 Inch				60 Inch			
Size	Item Number	B	T	Wt.	Item No	B	T	Wt.	Item No	B	T	Wt.
½"	ST0542SW90	54	12	6.20	ST0548SW90	60	12	6.90	ST0560SW90	72	12	8.30
¾"	ST0742SW90	54	12	8.20	ST0748SW90	60	12	9.10	ST0760SW90	72	12	11.00
1"	ST1042SW90	54	12	12.00	ST1048SW90	60	12	13.00	ST1060SW90	72	12	15.00
1-¼"	ST1242SW90	54	12	16.00	ST1248SW90	60	12	18.00	ST1260SW90	72	12	22.00
1-½"	ST1542SW90	54	12	19.00	ST1548SW90	60	12	21.90	ST1560SW90	72	12	25.00
2"	ST2042SW90	54	12	26.30	ST2048SW90	60	12	29.20	ST2060SW90	72	12	37.00
2-½"	ST2542SW90	54	12	42.00	ST2548SW90	60	12	46.70	ST2560SW90	72	12	56.00
3"	ST3042SW90	54	12	57.00	ST3048SW90	60	12	63.30	ST3060SW90	72	12	76.00
3-½"					ST3548SW90	60	12	75.00	ST3560SW90	72	12	90.00
4"					ST4048SW90	60	12	87.50	ST4060SW90	72	12	105.00
5"					ST5048SW90	60	12	116.70	ST5060SW90	72	12	140.00
6"					ST6048SW90	60	12	156.00	ST6060SW90	72	12	185.00