

Calconduit™

Rigid Conduit, Rigid & EMT Fittings

EMT Factory Elbows - 90°

Application:

EMT elbows are to be installed on conduit raceways for the interconnection of conduit runs and other fittings.

Features:


Fabricated from UL Listed Electrical Metallic Tubing (EMT)

Certifications and Compliances:

- UL & CUL Listed
- UL File Number E315441
- UL797 with statements of conformance
- ANSI C80.3
- National Electrical Code® 2008 -Article 358
- A.R.R.A. Available
- Federal Specification WW-C-563*

Options:

Available in any degree of bend from 5° to 90°, and special radius



90° Factory Elbows				Dimensions (inches)			
Item Number	Description	Wt. (lbs)	Box Qty	A	B	T	Cut Length
EM0590EL00	½" X 90°	1.00	50	4.0	6.9	2.9	12.0
EM0790EL00	¾" X 90°	1.30	50	4.5	7.4	2.9	12.9
EM1090EL00	1" X 90°	2.10	25	5.8	8.7	3.0	15.0
EM1290EL00	1-¼" X 90°	3.40	20	7.3	10.6	3.3	18.0
EM1590EL00	1-½" X 90°	4.80	15	8.3	11.9	3.6	20.3
EM2090EL00	2" X 90°	7.30	10	9.5	13.8	4.3	23.4
EM2590EL00	2-½" X 90°	13.90	50	10.5	15.8	5.3	27.0
EM3090EL00	3" X 90°	21.30	35	13.0	18.8	5.8	32.0
EM3590EL00	3-½" X 90°	27.00	35	15.0	21.8	6.8	37.0
EM4090EL00	4" X 90°	36.80	35	16.0	23.1	7.1	39.3

Calconduit

12021 Woodruff Ave., Downey, CA 90241

Ph: (562) 803.4388 Ph: (800) 225.7473 Fax: (562) 803.4488 | calconduit.com

