

PVC COATED LIQUIDTIGHT CONNECTORS - 90°

Description:

Calbond PVC coated liquidtight connectors are used with Liquidtight Conduit. The sleeve on the liquidtight connector is sized specifically to tighten around PVC conduit. Pulling compound is recommended for ease of installation. Fittings are provided with a flexible sleeve on the conduit side and a sealing form on both the box side and the mating part of the gland.

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1/2" to 2"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2"
- For sizes 2-1/2" - 4", the length of the sleeve extension(s) shall be at least 2"
- Available in straight, 45 degree or 90 degree body configurations

Standards:

- UL Standard 514B
- CSA Standard: C22.2 No. 18



90°					
Item Number	Trade Size	A	B	C	Weight Per 100 (lbs)
PV0300LT3890	3/8"	1.24	1.80	0.56	30
PV0500LT5090	1/2"	1.46	2.10	0.56	30
PV0700LT7590	3/4"	1.74	2.54	0.56	40
PV1000LT10090	1"	1.96	3.23	0.75	60
PV1200LT12590	1-1/4"	2.36	4.04	0.81	100
PV1500LT15090	1-1/2"	2.80	4.48	0.81	170
PV2000LT20090	2"	3.33	5.48	0.88	270
PV2500LT25090	2-1/2"	3.83	10.92	1.00	380
PV3000LT30090	3"	4.58	12.3	1.00	420
PV4000LT40090	4"	5.58	14.7	1.13	620

