

AFC Nonmetallic Whips Type UL

- Conduit**
Type LFNC-B, Nonmetallic Liquidtight
- Conductors**
THHN/THWN 8 & 10 AWG Stranded
- Maximum Temperature Rating**
90°C (Dry); 75°C (Wet)
- Grounding**
NEC® 250.118(1)
- Maximum Voltage Rating**
600V
- References & Ratings**
 - UL 83, 1660 and 514B, File Reference E96572
 - NEC® 410, 430, 440, 250, 356



Product Core	Trade Size (in)	Length (ft)	No. of Cond.	AWG (Cond. Size)	Put Up
Non-metallic Liquidtight Whips (Standard Configurations)					
8014	1/2"	4'	3	10	10 per box
8015	1/2"	6'	3	10	10 per box
8016	3/4"	4'	3	8	10 per box
8017	3/4"	6'	3	8	8 per box
8021	1/2"	4'	3	10	20 bulk
8022	1/2"	6'	3	10	15 bulk
8023	3/4"	4'	3	8	10 bulk
8024	3/4"	6'	3	8	10 bulk

Whips come with Black, Red, Green THHN/THWN conductors.
Other conductor colors available by special request.
All whips come with one straight non-metallic liquidtight connector and one 90° angle non-metallic liquidtight connector.

Pack N Roll™

Type MC and AC Cable Dispenser

- Description**
Our patented heavy duty cable accessory enables electrical contractors to perform remodel and small construction/service projects with ease.
- Catalog Number**
9989-BE
- Net Weight**
16.4 Lbs
- Dimensions**
19" Diameter
12-13/16" High
- Capacity**
250 Ft Coils

- Fast and Easy to Pull without any Tangles
- Reduces Cable Memory
- Stackable
- Eliminates Scrap
- Keeps Cable Organized, Neat and Clean
- Prevents Cable Damage

*Accommodates the majority of AFC's coil products

