

Calconduit™

Rigid and EMT Conduit & Fittings

A division of

CALPIPE INDUSTRIES™
Incorporated

GALVANIZED RIGID CONDUIT ELBOWS - 90°

Description:

Galvanized Rigid Conduit (GRC) Elbows are to be installed on conduit raceways for underground stub-ups, and interconnection of conduit runs and other fittings.

Features:


- Fabricated from UL listed hot-dipped galvanized rigid conduit
- Threaded ends (NPT)

Certifications and Compliances:

- UL & CUL Listed - UL6
- UL File Number E226472
- UL6 with statements of conformance
- ANSI C80.1
- CalTrans Specification 86-2.05
- A.R.R.A. Available
- ASTM A239

Options:

Available in any degree of bend from 5° to 90°, and special radius



Item Number	Size	Wt. (lbs)	Box Qty	A	B	C	Cut Length
ST0590EL00	1/2" X 90°	1.00	50	4.0	6.0	2.9	12.0"
ST0790EL00	3/4" X 90°	1.30	50	4.5	7.4	2.9	12.9"
ST1090EL00	1" X 90°	2.10	25	5.8	8.7	3.0	15.0"
ST1290EL00	1-1/4" X 90°	3.40	20	7.3	10.6	3.3	18.0"
ST1590EL00	1-1/2" X 90°	4.80	15	8.3	11.9	3.6	20.3"
ST2090EL00	2" X 90°	7.30	10	9.5	13.8	4.3	23.4"
ST2590EL00	2-1/2" X 90°	13.90	50	10.5	15.8	5.3	27.0"
ST3090EL00	3" X 90°	21.30	35	13.0	18.8	5.8	32.0"
ST3590EL00	3-1/2" X 90°	27.00	35	15.0	21.8	6.8	37.0"
ST4090EL00	4" X 90°	36.80	35	16.0	23.1	7.1	39.3"
ST5090EL00	5" X 90°	70.00	bulk	24.0	35.2	11.2	60.0"
ST6090EL00	6" X 90°	111.80	bulk	30.0	42.6	12.6	72.3"

All dimensions are for informational purposes only

**Tolerances +/-5%*

Calconduit

19440 Dominguez Hills Dr, Rancho Dominguez, CA 90220 • (P) 562.803.4388 • (F) 310.885.1894 • calconduit.com