



# U5200-XL-41



<b>Catalog Number</b>	U5200-XL-41
<b>Marketing Product Description</b>	Unmetered Small Closing Plate 520GR TT30 Single Pedestal Direct Bury
<b>UPC</b>	784572258174
<b>Length (IN)</b>	5.188
<b>Width (IN)</b>	8.688
<b>Height (IN)</b>	64.5
<b>Brand Name</b>	Milbank
<b>Type</b>	Unmetered Power Supply
<b>Special Features</b>	One Single Pole 20 Ampere Breaker and One Single Pole 30 Ampere Breaker
<b>Application</b>	RV Power
<b>Standard</b>	UL Listed;Type 3R
<b>Voltage Rating</b>	Up to 240 Volts Alternating Current
<b>Amperage Rating</b>	125 Continuous Ampere
<b>Phase</b>	1 Phase
<b>Frequency Rating</b>	60 Hertz
<b>Size</b>	5.188L x 8.688W x64.5H
<b>Number Of Cutouts</b>	2
<b>Cutout Size</b>	One Single Pole 20 Ampere Breaker and One Single Pole 30 Ampere Breaker
<b>Cable Entry</b>	Underground

<b>Terminal</b>	Double Mechanical
<b>Insulation</b>	Glass Polyester
<b>Mounting</b>	Pedestal
<b>Enclosure</b>	G90 Galvanized Steel with Powder Coat Finish
<b>Jaw Quantity</b>	4 Terminal
<b>Bypass Type</b>	No Bypass
<b>Number of Meter Positions</b>	Single Power Head
<b>Equipment Ground</b>	2 Barrel Ground Lug and Ground Bar
<b>Hub Opening</b>	Small Closing Plate
<b>Line Side Wire Range</b>	6 AWG - 350 kcmil
<b>Number Branch Circuits</b>	4
<b>Number Of Receptacles</b>	2
<b>Receptacle Configuration</b>	One NEMA TT30 and One NEMA 5-20 Ground Fault

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.