

Dieless Remote Power Operated Compression Tool



TYPE IDT-6H

Features

- Dieless operation
- Flip top head
- Lightweight 6.2 lbs
- Equipped with 3/8" male screw coupler

Benefits

- No dies to lose or replace, one tool does it all
- Easy connector loading and unloading
- Easy to hold, less tiring for numerous crimps
- For use with standard industry hoses

Specifications

Force developed: 6.2 Tons
Operating pressure: 10,000 PSI
Overall Length: 10-1/2"
Weight: 6.2 lbs.
Conductor Range: 750kcmil-8 AL
750kcmil-6 CU



| For Use with | |
|---------------------------------|------------------------------|
| Aluminum Connectors | Copper Connectors |
| ACL, ACN Series thru 750kcmil | CLN4, CLN9, CLND, CSLT, CLWU |
| 2ACL, 2ACN Series thru 750kcmil | CLNF, CLNN, CLNS, |
| AS Series thru 750kcmil | CLNU, CLW4, CLW9, |
| IACL Series thru 500kcmil | CLWD, CLWF, CLWN, |
| 2IACL Series thru 500kcmil | CLWS, CSN4, CSN9, |
| Series: ALNS, ALND, ASN, | CSND, CSNF, CSNN, |
| ALNN thru 750kcmil | CSNS, CSW4, CSW9, |
| | CSWD, CSWF, CSWN, |
| | CSWS thru 750kcmil |

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Additional Requirements:

- Hose
- Pump

Includes:

Steel Carrying Case Instruction Manual

J