

Project: _____

Location: _____

Product Type: _____

Contact/Phone: _____

Model #: _____

K4100 & K4400 Series

Stem Mounting

The K4100 & K4400 Series Photocontrols feature stem mounting, thermal-type, controls with single and multi-voltage models. Thermal-type photocontrols provide dusk-to-dawn lighting control and a delay action, which eliminates loads switching OFF due to car headlights, and lightning. The thermal-type controls feature a cadmium sulfide photocell and a sonic-welded polycarbonate case and lens to seal out moisture. The design utilizes a dual temperature compensating bimetal and composite resistor for reliable long life operation over ambient temperature extremes. These models are California Title 24 compliant.

Features

- Cadmium sulfide photocell
- Sonic welded polycarbonate housing and lens to seal out moisture
- Delay action eliminates load switching OFF due to car headlights, and lightning
- 6" leads
- Light level slide adjustment
- Controls come with a washer gasket and locking nut
- "M" Models are heavy duty die cast housings

Ratings

Size: 1 9/16" (4.0 cm) square, 3" (7.6 cm) long
 Models with "M"- 1 15/16" (4.9 cm) square, 3 3/4" (9.5 cm) long

Color: Gray

Electrical Rating: See table

Activation: 1-5 FC ON; 3-15 FC OFF
 (photo eye clear on models with shield)

Power Consumption: Averages under 1 Watt

Operating Temperature: -40°F to 158°F (-40°C to 70°C)

Shipping Weight: .14 lb. (.06 kg)
 Models with "M"- .62 lb (.28 kg)

Agency Listing: See table



Model Number	Tungsten (Watts)	Ballast (VA)	Tungsten (Amps)	Ballast (Amps)	VAC	Agency Listing
K4121C	1800	1000	15	8.3	120	UL
K4421M	1800	1000	15	8.3	120	CSA, C/UL
K4123C	3100-4150	1700-2300	15	8.3	208-277	CSA, C/UL
K4423M	3100-4150	1700-2300	15	8.3	208-277	UL, CSA
K4127	5205	2880	15	8.3	347	CSA, C/UL
*K4135	7200	4000	15	8.3	480	
*K4136M	2000-4625	1800-4150	16.7	15	120 or 277	
*K4141C	3000	3000	25	25	120	

*Models are not agency certified

Specification

The photocontrol shall provide automatic switching for outdoor lighting loads. The control shall be a thermal design with built-in delay to ensure that the controlled lighting does not switch off due to ambient light or light striking the photocell. The photocontrol shall have a rating of ____Watts and ____Amps tungsten and ____Watts and ____Amps ballast based on agency testing at 50% power factor for ballast loads. The photocontrol shall provide switching for nominal voltage fixtures of ____Volts $\pm 10\%$ to accommodate fluctuations in supply voltage. The photocontrol shall be the stem mounting type, with all necessary mounting hardware and instructions. The photocontrol housing shall be constructed of _____(polycarbonate)(die cast metal). The photocontrol components shall consist of a metal film resistor, dual temperature compensating bi-metal blades, snap action contact blades, chemically treated/polymer encapsulated cadmium sulfide photocell and silver alloy contacts to ensure reliable operation. The photocontrol shall be 100% factory tested for function within specified light levels. The photocontrol shall be agency certified (unless otherwise noted) and tested accordingly. The photocontrol shall function over temperature range of -40°F to 158°F (-40°C to 70°C). The photocontrol shall be Intermatic model _____(See Model Numbers Listed).

Diagrams

