

Kwikflex® NMLT Multi-Angle Conduit Connectors

Kwikflex™ nonmetallic liquidtight flexible (NMLT) conduit and fittings offer superior flexibility and corrosion resistance for protecting electrical wiring and connections to commercial and residential pool and spa motors, air conditioners, pumps and outdoor lighting.

Approved for use in dry, damp or wet locations, Kwikflex™ provides a positive, waterproof seal and easy, screw-together connectivity in indoor/outdoor, exposed or concealed environments. Kwikflex NMLT is UL listed and permitted for use by the NEC (Article 356) in exposed and concealed locations for the protection of conductors where a degree of flexibility is required.

FEATURES & BENEFITS

- Listed under the Underwriter's Laboratories
- Available in 1/2" and 3/4" sizes
- All nylon construction resists salt water, weak acids, gasoline, alcohol, oil, grease and common solvents
- No disassembly required. Instead, the installer simply pushes the conduit or tubing onto the ferrule, tightening the domed sealing nut. The completed assembly can then be secured in the chassis by the locknut (or first secure the connector into an NPT threaded hole)
- Standard color Gray
- Eliminate inventory, as the swivel design can be substituted for a Straight or 90° connector
- Molded of type nylon 6. Flammability classification 94V-2: temperature index 125°C
- Suitable for indoor/outdoor use
- "O" Ring and steel locknut included

STANDARDS



APPLICATIONS

- HVAC equipment
- Machine tools
- Marine equipment
- Motors & controls
- Printing equipment
- Pumps
- Refrigeration equipment
- Transformer connections
- Outdoor lighting

SPECIFICATIONS

Part No.	Product Code	Trade Size	K.O. Size	Std. Pkg	Weight / Pkg.	Part Dimensions (inches)					
						Pos.1 Dimension			Pos.2 Dimension		
						A	B	C	A	B	C
LTMA10	065016	1/2"	1/2"	100	7	3.35	2.15	0.500	3.025	2.395	0.500
LTMA15	065016	3/4"	3/4"	100	7	4.30	2.65	0.520	3.850	3.350	0.520

Available in Black upon request

