

8U Series LED Collection

6.5" Premium LED Under Cabinet 3000K - WHT

8U30KD07WHT (Textured White)



Dimensions

|        |       |
|--------|-------|
| Height | 6.50" |
| Length | 4.00" |
| Width  | 4.00" |

Project Name: \_\_\_\_\_

Location: \_\_\_\_\_

Type: \_\_\_\_\_

Qty: \_\_\_\_\_

Comments: \_\_\_\_\_

Ordering Information

|                    |                          |
|--------------------|--------------------------|
| Product ID         | 8U30KD07WHT              |
| Finish             | Textured White           |
| Available Finishes | BZT, NIT, WHT            |
| Collection         | 8U Series LED Collection |

Dimensions

|        |          |
|--------|----------|
| Weight | 0.90 LBS |
|--------|----------|

Photometrics

|                       |       |
|-----------------------|-------|
| Kelvin Temperature    | 3000K |
| Color Rendering Index | 92    |
| Volt AMPERE           | 6.5   |

Specifications

|                      |                  |
|----------------------|------------------|
| Material             | Steel / Aluminum |
| Diffuser Description | Frosted          |

Electrical

|                         |                |
|-------------------------|----------------|
| Dimmable                | Yes            |
| Voltage                 | 108-132V       |
| Input Voltage           | Single(120)    |
| Operating Voltage Range | 108-132V       |
| Switch Type             | On-Off, Rocker |

Qualifications

|                    |                                                                        |
|--------------------|------------------------------------------------------------------------|
| Safety Rated       | Dry                                                                    |
| Title 24           | Yes                                                                    |
| Expected Life Span | 50000 Hours                                                            |
| Warranty           | <a href="http://www.kichler.com/warranty">www.kichler.com/warranty</a> |

Installation

|                     |         |
|---------------------|---------|
| Wire Connectors     | Push In |
| Direct Wire         | Yes     |
| Knockouts           | 0.5 in  |
| Number of Knockouts | 2       |

Primary Lamping

|                    |            |
|--------------------|------------|
| Light Source       | LED        |
| Lamp Included      | Integrated |
| Delivered Lumens   | 214        |
| Delivered Efficacy | 56         |
| Dimming            | Yes        |