

# Flush Mount LED 3000K Flush Mount LED WHT

43848WHLED30 (Textured White)



## Dimensions

Height	1.25"
Width	7.50"

Project Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Type: \_\_\_\_\_  
Qty: \_\_\_\_\_  
Comments: \_\_\_\_\_

## Ordering Information

Product ID	43848WHLED30
Finish	Textured White
Available Finishes	WHT, WHT, NI, NI, NI, NI, OZ, OZ, OZ, WHT, WHT, WHT, WHT

## Dimensions

Height from center of Wall opening	3.75"
Base Backplate	7.50 DIA
Weight	1.00 LBS

## Photometrics

Kelvin Temperature	3000 K
Color Rendering Index	90

## Specifications

Material	Steel
Diffuser Description	Polycarbonate Diffuser

## Electrical

Dimmable	Yes
Dimmable Notes	This LED is compatible with most standard incandescent dimmers, LED dimmers, and electronic low voltage dimmers. For more information, go to Kichler.com/dimming
Voltage	120 V
Input Voltage	Single(120)

## Qualifications

Safety Rated	Wet
ADA Compliant	Yes
Expected Life Span	40000 Hours
Warranty	<a href="http://www.kichler.com/warranty">www.kichler.com/warranty</a>

## Primary Lamping

Light Source	LED
Lamp Included	Integrated
Light Source Equivalent	75(1) Incandescent
# of Bulbs/LED Modules	1
Delivered Lumens	1000
Delivered Efficacy	67

### Kichler

7711 East Pleasant Valley Road  
Cleveland, Ohio 44131-8010  
Toll free: 866.558.5706 or [kichler.com](http://kichler.com)

### Notes:

1) Information provided is subject to change without notice.  
All values are design or typical values when measured under laboratory conditions.  
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

**KICHLER**

# Flush Mount LED 3000K Flush Mount LED WHT

43848WHLED30 (Textured White)

Project Name: \_\_\_\_\_

Location: \_\_\_\_\_

Type: \_\_\_\_\_

Qty: \_\_\_\_\_

Comments: \_\_\_\_\_

Dimming

Yes

## Kichler

7711 East Pleasant Valley Road  
Cleveland, Ohio 44131-8010  
Toll free: 866.558.5706 or [kichler.com](http://kichler.com)

## Notes:

1) Information provided is subject to change without notice.  
All values are design or typical values when measured under  
laboratory conditions.

2) Incandescent Equivalent: The incandescent equivalent as  
presented is an approximate number and is for reference only.

**KICHLER**