

SUBMITTAL SHEET

JOB NAME	ITEM TAG
JOB LOCATION	PART NUMBER
CONTRACTOR	DATE
ENGINEER APPROVAL	DATE

LEAD-FREE CAST PRESSURE FITTINGS

CAST BRASS DROP-EAR ELBOWS

Lead-free design is suitable for all State and pending U.S. Federal Public Law (111-380) potable water installations.

Drop-ear holes accept most screw fastener types, permitting easy attachment to cross-brackets.

Integral drop-ears and flat-back elbow shape, place more of the elbow's surface against the bracket, enhancing stability when installing the shower arm

Full-length drop-ears extend beyond the elbow's body, providing ample tool access when driving screws


FNPT threads (where applicable) are precision-cut to accommodate plated shower arms

Working Pressure, Non Shock (PSI)

125 CWP

Not suitable for steam service

- End connections comply with ANSI / ASME B1.20.1 and ANSI / ASME B16.18
- Truesdail Labs third-party tested and certified in compliance with current State and pending National (U.S. Federal Public Law 111-380) lead-free plumbing laws.
- Manufactured in an ISO accredited facility



MATERIAL SPECIFICATION

PART	MATERIAL	SPECIFICATION
1 Fitting body	Lead-free brass alloy	UNS C89540

Dimensions

Size	A	B	C (corner-to-corner / flat-to-flat)	D	E	F
3/8" FNPT x 1/2" Sweat	1.29	1.12	0.89 / 0.83	2.09	1.63	0.13
1/2" FNPT x 1/2" Sweat	1.41	1.14	1.05 / 0.98	2.09	1.63	0.13
1/2" Sweat x 1/2" Sweat	0.93	1.34	0.77	2.09	1.63	0.13

