

NV-T2FAM Tuner.

Specifications

Power Requirements

AC Power Input	90-264 VAC 50/60Hz
Power Consumption, operating	3 W max.
Power Consumption, standby	1 W max.
Memory Backup	Indefinite

Auto Scan Sensitivity	Adjustable
Image Rejection	50dB min.

Audio Output

Level	Two Stereo Outputs
Impedance	Adjustable 560 ohm

FM

Tuning Range	87.5 to 108.0 MHz
Total Harmonic Distortion (1kHz)	
Mono	0.3%
Stereo	0.5%
Signal to Noise Ratio	
Mono	80dB
Stereo	75dB
Usable Sensitivity	1.0 μ V
Selectivity (400 kHz)	50dB
Frequency Response (20 Hz to 15 kHz)	-3dB
Stereo Separation (1 kHz)	43dB
Antenna Input	75 Ω (unbalanced)
Usable Sensitivity, 30dB S/N	14dBV
Auto Scan Sensitivity	Adjustable
Image Rejection	50dB min.
Limiting Sensitivity	10dBV
Intermediate Frequency	10.7 MHz

Infrared Input

Input Voltage	3-15 V
Input Carrier Frequency	38 kHz nominal
Polarity	Active High

Regulatory Approvals

USA Safety Listing (UL 6500)
FCC
Canada Safety Listing (CAN/CSA E60065.00)

Physical Specifications

Unit Size (mm)	44 H x 430 W x 250 D
Unit Size (inch)	1.75 H x 17 W x 9.875 D
Shipping Size (mm)	205 H x 515 W x 343 D
Shipping Size (inch)	8 H x 20 1/4 W x 13 1/2 D
Unit Weight (kg)	2.36
Unit Weight (lbs)	5.20
Shipping Weight (kg)	6.5
Shipping Weight (lbs)	14.3

AM

Tuning Range	522 to 1720 kHz
Signal to Noise Ratio	50dB
Usable Sensitivity	18 μ V
Intermediate Frequency	450 kHz
Usable Sensitivity, 25dB S/N	14dBV

NuVo reserves the right to change specifications without notice.

Office Toll Free: 866.796.4904

Office Direct: 859.817.7200

Email: sales@nuvotechnologies.com

Web: www.nuvotechnologies.com