

Pass and Seymour Flexcor® Support Grips Service and Bus Drop, Single Eye, Cable Diameter 0.53 - 0.73 in. Part No. FC52



FC52: Bus Drop, Closed Mesh, Single Eye, Cable Diameter 0.53 - 0.73 inches, Bale Length 9-in, Mesh Length 6.5-in, Break Strength 1100 lbs.

Features & Benefits

Bus drop grips are used as cable support. They relieve any direct tension from the critical connection and absorb vibration and flexing.

They are offered with either the single eye or locking bale attachment.

Most Flexcor products have UL and/or CSA approvals. Please contact factory for approval information.

Bus drop grips are woven of galvanized steel wire.

Support grips are woven of corrosion-resistant tinned-stainless steel wire.

Bale Length: 9: Mesh Length: 6.5

Specifications

Pass & Seymour	UPC Number	785007998733
Mexico	Construction	Various Types of Pulling, Support and Strain Relief Grips
Industrial	Standard	UL/CSA Approval (consult factory)
Support Grip		
0.73 in	Product Length US	6.5 in
6.5 in	Cable Diameter Range	0.530-0.730 in
ty Agencies		
Yes	CSA File Number	67507
1100 lb	Maximum Cable Range	0.53 in
Single	Minimum Cable Range	0.73 in
Various Cable Diameter Ranges	Indoor/Outdoor	Both
	Mexico Industrial Support Grip 0.73 in 6.5 in ty Agencies Yes 1100 lb Single	Mexico Construction Industrial Standard Support Grip 0.73 in Product Length US 6.5 in Cable Diameter Range ty Agencies Yes CSA File Number 1100 lb Maximum Cable Range Various Cable Diameter Range

Consult the Factory for Mounting Recommendations

Mounting