

Pass and Seymour **20A 125/250V NEMA L1420 Single Receptacle, 4-Wire, Black** Part No. L1420R



Turnlok® Single Receptacle 4-Wire 20A 125/250V

Features & Benefits

Compact, impact-resistant nylon face and body are ultrasonically welded together for unrivaled strength.

One piece, high-grade brass contacts offer excellent conductivity and heat-rise resistance.

Single-piece, solid brass mounting strap is free of easily loosened rivets found on other brands.

.032 inch thick, brass, triple-wipe power contacts for lasting retention.

Clearly marked NEMA configuration, rating, and third-party listing on each unit's face.

Side and external screw-pressure-plate back wire capability.

Specifications

General Info

Pass & Seymour	Color	Black
Matte	UPC Number	785007142051
Mexico	Number of Receptacles	1
Brass Mounting Strap, Impact Resistant	Outlet Type	Locking
Commercial, Industrial	Wall Plate Included	No
UL 498, FEDSPEC	Warranty Type	1-Year Limited Warranty
Outlet		
	Matte Mexico Brass Mounting Strap, Impact Resistant Commercial, Industrial UL 498, FEDSPEC	Matte UPC Number Mexico Number of Receptacles Brass Mounting Strap, Impact Resistant Outlet Type Commercial, Industrial Wall Plate Included UL 498, FEDSPEC Warranty Type

Dimensions

Product Width US	1.61 in	Product Depth US	1.19 in	
Product Height US	2.29 in			
Listing Agencies / 3rd Party Agencies				
cULus ListingNumber	140596	cULus Listed	Yes	
Additional Information				
Product Environmental Profile	Yes			
Technical Information				
Connection Location	Back and Side	Number of Wires	4	
Amperage	20 A	Number of Poles	3-Way	
Wire Size	4 AWG	Indoor/Outdoor	Indoor	
NEMA Configuration Code	L14-20R	Mounting Type	Вох	
Wire Connection Type	Screw Terminals	Voltage	125/250 V	