

Single-Pole, Double Combination Switch, 20A, 120/277V, White.



Features & Benefits

Easily accessible break-off separate or common feed.

Long-life red neon lamp in pilot light rated 1/25 Watt, 125V.

Side wire #12 and #14 AWG.

Two devices fit into the space of one.

Grounding combination devices meet NEC Tamper-resistant version features dual mechanical shutter system to help prevent insertion of foreign objects.

For covering patents, see www.legrand.us/patents.

Specifications

General Info

| | | | |
|--------------------|--------------------------|---------------------|-------------------------|
| Product Line | Pass & Seymour | Color | White |
| Finish | Satin | UPC Number | 785007006049 |
| Country Of Origin | Mexico | Features | Combination |
| Switch Type | Toggle | Number of Switches | 2 |
| Application Sector | Hospitality, Residential | Wall Plate Included | No |
| Standard | UL20 | Warranty Type | 1-Year Limited Warranty |
| Type | Combination | | |

Dimensions

| | | | |
|---------------------------------------|--|--------------------------|-----------------------|
| Product Width US | 1.32 in | Product Depth US | 0.94 in |
| Product Height US | 4.06 in | | |
| Listing Agencies / 3rd Party Agencies | | | |
| cULus ListingNumber | 140597 | cULus Listed | Yes |
| Technical Information | | | |
| Load Rating | 20 A @ 120/277 VAC | Contact Configuration | N-0 |
| Operating Cycles | 30000 | Connection Location | Side Only |
| Terminal Accommodation | #14 AWG - #12 AWG | Number of Gangs | 1 |
| Throw Type | Single Throw | Amperage | 20 A |
| Number of Poles | Single Pole | Requires Neutral Wire | Yes |
| Indoor/Outdoor | Indoor | Mounting Type | Wall Box |
| Wire Connection Type | Screw Terminals | Voltage | 120/277 V |
| Load Type | CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon | Environmental Conditions | Flammability: UL94 V2 |