

Three Pole, Three Phase AC Manual Motor Controller, suitable as Motor Disconnect - 10KA @ 600VAC, 30A max. Class J Fuse.



## Features & Benefits

High Horsepower rating of 20HP

Gull-wing shaped brass terminal pressure clamps

Constructed of glass-reinforced thermoplastic

UL508 and cULus Listing of individual device and assembled device within enclosure

Heavy-duty zinc-plated steel strap, two brass rivets secure strap to housing

Two-point contact arm design reduces overall unit size

Two oversized silver alloy contacts withstand years of use; improve heat dissipation by distributing arc energy

One-piece contact carrier constructed of glassreinforced thermoplastic ensures long-lasting ""make and break"" performance

## Specifications

### General Info

|                    |                        |                     |                                    |
|--------------------|------------------------|---------------------|------------------------------------|
| Product Line       | Pass & Seymour         | Color               | Black                              |
| Finish             | Matte                  | UPC Number          | 785007267686                       |
| Country Of Origin  | Mexico                 | Features            | Heavy Duty Zinc Plated Steel Strap |
| Switch Type        | Toggle                 | Number of Switches  | 1                                  |
| Application Sector | Commercial, Industrial | Wall Plate Included | No                                 |
| Standard           | CSA Listed, UL Listed  | Warranty Type       | 1-Year Limited Warranty            |
| Type               | Manual Controller      |                     |                                    |

Dimensions

|                   |          |                  |          |
|-------------------|----------|------------------|----------|
| Product Width US  | 1.825 in | Product Depth US | 1.753 in |
| Product Height US | 3.67 in  |                  |          |

Listing Agencies / 3rd Party Agencies

|              |     |
|--------------|-----|
| cULus Listed | Yes |
|--------------|-----|

Technical Information

|                       |  |                          |                   |
|-----------------------|--|--------------------------|-------------------|
| Load Rating           | 30 A @ 600 VAC   | Operating Cycles         | 50000             |
| Connection Location   | Back and Side  | Terminal Accommodation   | #14 AWG - #10 AWG |
| Number of Gangs       | 1  | Throw Type               | Single Throw      |
| Amperage              | 30 A   | Number of Poles          | 3-Way             |
| Requires Neutral Wire | Yes  | Indoor/Outdoor           | Indoor            |
| Mounting Type         | Wall Box   | Number of Phases         | 3                 |
| Wire Connection Type  | Screw Terminals  | Voltage                  | 600.0 V           |
| Load Type             | CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon | Environmental Conditions | UL94 V2           |