

# **GETTING UP TO SPEED**

## with Legrand's Residential USB Charging Solutions

When it comes to adding the convenience of built-in USB charging to residential projects, it's no longer "one speed fits all." Legrand offers USB Outlets from three tiers of charging speeds to fit any project's needs or customer's preference.

#### **THE GOOD**



Trademaster® 3-Way Switch with USB Type-A/A Outlet

2.1A charging capacity across all ports.

TM83USBWCCV4



radiant® 15A & 20A Tamper-Resistant Self-Test GFCI USB Type-A/A Outlet

2A charging capacity between both ports.

1597TRUSBAA**X** BK, DB, G, GRY, I, LA, NI, W 2097TRUSBAA**X** Brown, BK, GRY, I, LA, RED, W



radiant® 15A & 20A Tamper-Resistant Self-Test GFCI USB Type-A/C Outlet

2A charging capacity between both ports.

1597TRUSBAC**X**Brown, BK, GRY, I, LA, W
2097TRUSBAC**X**Brown, BK, DB, GRY, I, LA, RED, W



radiant® 15A & 20A Tamper-Resistant Outdoor Self-Test GFCI **USB Type-A/C** Outlet

2A charging capacity between both ports.

1597TRWRUSBACX BK, GRY, I, W 2097TRWRUSBACX BK, GRY, W



BETTER

radiant® 15A & 20A Tamper-Resistant Outdoor Self-Test GFCI **USB Type-C/C** Outlet

2A charging capacity between both ports.

1597TRWRUSBCCW W 2097TRWRUSBCCW



radiant® Quad USB Type-A Charger

4.2A charging capacity across all ports.

TM8USB4XCC6 BK, I, LA, NI, W



radiant® 15A Tamper-Resistant **USB Type-A/A** Outlet

3.1A charging capacity between both ports.

TM826USB**X** BK, G, I, LA, NI, W



radiant® Wireless Charger with 15A Tamper-Resistant **USB Type-A** Outlet

5W Qi wireless charging pad; 3.1A charging capacity for Type-A port.

RWC826USB**X**CCV2 BK, I, LA, W



radiant® 15A Tamper-Resistant USB Type-A/C Outlet

3.1A charging capacity between both ports.

R26USBAC**X** BK, DB, G, I, LA, NI, W



adorne® **USB Type-A**Outlet Module, Half-Size
2.1A charging capacity.

ARUSBM4



adorne® 15A Tamper-Resistant Dual-USB Type-A/A Outlet

3.1A charging capacity between both ports.

ARTRUSB153**X**4 G, M, W



WHAT IS USB TYPE-C? USB Type-C is the latest standard for charging. With its smaller connector head and symmetrical, reversible orientation, it fits easily into phones, tablets, laptops and more. Type-C can provide higher power for faster charging.

## THE BETTER Charge phones, tablets & more up to 40% faster.





radiant® 15A Tamper-Resistant Ultra-Fast USB Type-A/C Outlet

6A charging capacity; 5V output; 15W per port.

R26USBAC6X BK, DB, G, I, LA, NI, W



radiant® 15A Tamper-Resistant Ultra-Fast USB Type-C/C Outlet

6A charging capacity; 5V output; 15W per port.


R26USBCC6**X** BK, DB, G, I, LA, NI, W



radiant® Tamper-Resistant Outdoor Ultra-Fast

6A charging capacity; 5V output; 15W per port.

WRR26USBAC6**X** BK, I, LA, W



adorne® 15A & 20A Tamper-Resistant Ultra-Fast USB Type-A/C Outlet

6A charging capacity; 5V output; 15W per port.

ARTRUSB156AC**X**4 G, M, W ARTRUSB206AC**X**4 G, M, W



adorne® Ultra-Fast **USB Type-A/C** Outlet Module

6A charging capacity; 5V output; 15W per port.

ARUSB2AC6X4 G, M, W



Trademaster® 20A
Tamper-Resistant
Ultra-Fast

USB Type-A/C Outlet 6A charging

6A charging capacity; 5V output; 15W per port.

TR20USBAC6**X**Brown, BK, G, GRY, I,
LA, NI, RED, W



Trademaster® 20A Tamper-Resistant Ultra-Fast

**USB Type-C/C** Outlet 6A charging capacity; 5V output;

apacity; 5V output; 15W per port.

TR20USBCC6**X**Brown, BK, GRY, I,
LA, W

WHAT IS POWER DELIVERY? Power Delivery (PD) is a technology standard that has revolutionized charging. Supplying a higher level, it delivers faster, safer charging to the latest PD-enabled devices and is the ideal, future-proof solution for tablets, laptops and other devices that require more power for optimized charging speeds. Using a PD-enabled USB in-wall charger is the ideal way to be certain all devices are receiving the highest level of power they can accept for the fastest charge.

### THE BEST Charge phones, tablets and more up to 2X faster.



radiant® 15A & 20A Tamper-Resistant
Ultra-Fast Plus Power Delivery **USB Type-C/C** Outlet

5V, 9V & 15V output; 30W per port. Multilayered overcurrent protection. Indicator light for charging status.

R26USBPD**X**CC6 Brown, BK, DB, G, GRY, I, LA, NI, W TR20USBPD**X** 

Brown, BK, DB, G, GRY, I, LA, NI, RED, W



adorne® Ultra-Fast Plus Power Delivery
USB Type-C/C Outlet Module

5V, 9V & 15V output; 30W per port. Multilayered overcurrent protection. Indicator light for charging status.

> ARUSB30PD**X**4 G, M, W





adorne® 15A & 20A Tamper-Resistant Ultra-Fast Plus Power Delivery **USB Type-C/C** Outlet

BETTER

5V, 9V & 15V output; 30W per port. Multilayered overcurrent protection. Indicator light for charging status.

> ARTRUSB15PD30**X**4 G, M, W ARTRUSB20PD30**X**4 G, M, W

BASE SKU	LINE / COLLECTION	RATINGS	NOTES	COLORS	USB PORT TYPE(S)	CHARGING Wattage		TR	WR
ARTRUSB153X4	adorne	15A, 120V		G, M, W	Α, Α		3.1A (between both ports)	<b>√</b>	
ARUSBM4	adorne		USB only	М	А		2.1A		
1597TRUSBAAX	radiant	15A, 120V	with GFCI	BK, DBC4, G4, GRY, I, LA, NIC4, W	A, A		2A (between both ports)	<b>√</b>	
2097TRUSBAAX	radiant	20A, 120V	with GFCI	– , BK, GRY, I, LA, RED, W	Α, Α		2A (between both ports)	<b>√</b>	
1597TRUSBACX	radiant	15A, 120V	with GFCI	– , BK, GRY, I, LA, W	A, C		2A (between both ports)	<b>√</b>	
2097TRUSBACX	radiant	20A, 120V	with GFCI	– , BK, DBC4, GRY, I, LA, RED, W	A, C		2A (between both ports)	<b>√</b>	
1597TRWRUSBACX	radiant	15A, 120V	with GFCI	BK, GRY, I, W	A, C		2A (between both ports)	<b>√</b>	<b>√</b>
2097TRWRUSBACX	radiant	20A, 120V	with GFCI	BK, GRY, W	A, C		2A (between both ports)	<b>√</b>	<b>√</b>
1597TRWRUSBCCW	radiant	15A, 120V	with GFCI	W	C, C		2A (between both ports)	<b>√</b>	<b>√</b>
2097TRWRUSBCCW	radiant	20A, 120V	with GFCI	W	C, C		2A (between both ports)	<b>√</b>	<b>√</b>
R26USBACX	radiant	15A, 120V		BK, DBCCV4, G, I, LA, NICCV4, W	A, C		3.1A (between both ports)	<b>√</b>	
RWC826USBXCCV2	radiant	15A, 120V	with Qi Wireless Charging Pad	BK, I, LA, W	А	5W (Qi wireless charging pad)	3.1A (USB port)	<b>√</b>	
TM826USBX	radiant	15A, 120V		BK, GCCV4, I, LA, NICC6,W	Α, Α		3.1A (between both ports)	<b>√</b>	
TM8USB4XCC6	radiant		USB only	BK, I, LA, NI, W	A, A, A, A		4.2A (across all four ports)		
TM83USBWCCV4	Trademaster	15A, 120V	Switch combination device	W	A, A		2.1A (between both ports)		
ARTRUSB156ACX4	adorne	15A, 120V		G, M, W	A, C	15W (per port)	6A, 5V Output	<b>√</b>	
ARTRUSB206ACX4	adorne	20A, 120V		G, M, W	A, C	15W (per port)	6A, 5V Output	✓	
ARUSB2AC6X4	adorne		USB only	G, M, W	A, C	15W (per port)	6A, 5V Output		
R26USBAC6X	radiant	15A, 120V		BK, DBCCV4, G, I, LA, NICCV4, W	A, C	15W (per port)	6A, 5V Output	<b>√</b>	
R26USBCC6X	radiant	15A, 120V		BK, DBCCV4, G, I, LA, NICCV4, W	C, C	15W (per port)	6A, 5V Output	<b>√</b>	
WRR26USBAC6X	radiant	15A, 120V		BK, I, LA, W	A, C	15W (per port)	6A, 5V Output	✓	<b>√</b>
TR20USBAC6X	Trademaster	20A, 120V		– , BK, G, GRY, I, LA, NI, RED, W	A, C	15W (per port)	6A, 5V Output	<b>√</b>	
TR20USBCC6X	Trademaster	20A, 120V		– , BK, GRY, I, LA, W	C, C	15W (per port)	6A, 5V Output	<b>√</b>	
ARTRUSB15PD30X4	adorne	15A, 120V	with Power Delivery; multi-layered overcurrent protection; charging status indicator light	G, M, W	C, C	30W (per port)	5V, 9V & 15V output	<b>√</b>	
ARTRUSB20PD30X4	adorne	20A, 120V	with Power Delivery; multi-layered overcurrent protection; charging status indicator light	G, M, W	C, C	30W (per port)	5V, 9V & 15V output	<b>√</b>	
ARUSB30PDX4	adorne		USB only, with Power Delivery; multi-layered overcurrent protec- tion; charging status indicator light	G, M, W	C, C	30W (per port)	5V, 9V & 15V output		
R26USBPDX	radiant	15A, 120V	with Power Delivery; multi-layered overcurrent protection; charging status indicator light	- , BK, DBCC6, GCC6, GRY, I, LA, NICC6, W	C, C	30W (per port)	5V, 9V & 15V output	<b>√</b>	
TR20USBPDX	radiant	20A, 120V	with Power Delivery; multi-layered overcurrent protection; charging status indicator light	- , BK, DBCCV4, G, GRY, I, LA, NI, RED, W	C, C	30W (per port)	5V, 9V & 15V Output	<b>√</b>	

**Graphite** G

**Dark Bronze** 

DB

Nickel

NI

Magnesium

М

Black

ВК

lvory

Gray

GRY

Brown

**Light Almond** 

LA

White

W

Red

RED