



Pass and Seymour
30A L2130 Single Receptacle
Part No. L2130R

Turnlok® Single Receptacle 5-Wire 30A 3-Phase 120/208V



Features & Benefits

Compact, impact-resistant nylon face and body are ultrasonically welded together for unrivaled strength.

One piece, high-grade brass contacts offer excellent conductivity and heat-rise resistance.

Single-piece, solid brass mounting strap is free of easily loosened rivets found on other brands.

Accepts #14 - #10 AWG.

Face color coding by voltage facilitates locating and mating of proper devices.

Clearly marked NEMA configuration, rating, and third-party listing on each unit's face.

Side and external screw-pressure-plate back wire capability.

Specifications

General Info

| | | | |
|-----------------------|-------------------------|--------------------|--|
| Product Line | Pass & Seymour | Color | Black |
| UPC Number | 785007213058 | Country Of Origin | Mexico |
| Number of Receptacles | 1 | Features | Brass Mounting Strap, Impact Resistant |
| Outlet Type | Locking | Application Sector | Commercial, Industrial |
| Wall Plate Included | No | Standard | UL 498, Fedspec |
| Warranty Type | 1-Year Limited Warranty | | |

Dimensions

| | | | |
|---------------------------------------|---------------|----------------------|-----------------|
| Product Width US | 1.61 in | Product Depth US | 1.28 in |
| Product Height US | 2.42 in | | |
| Listing Agencies / 3rd Party Agencies | | | |
| cULus ListingNumber | 140596 | cULus Listed | Yes |
| Additional Information | | | |
| Product Environmental Profile | Yes | | |
| Technical Information | | | |
| Connection Location | Back and Side | Number of Wires | 5 |
| Amperage | 30 A | Number of Poles | 4-Way |
| Wire Size | 14 - 10 AWG | Indoor/Outdoor | Indoor |
| NEMA Configuration Code | L21-30R | Wire Connection Type | Screw Terminals |
| Voltage | 120/208 V | | |