



Double 3-way Combination Switch, 15A, 120/277V

## Features & Benefits

Easily accessible break-off separate or common feed.

Long-life red neon lamp in pilot light rated 1/25 Watt, 125V.

Side wire #12 and #14 AWG.

Two devices fit into the space of one.

Grounding combination devices meet NEC Tamper-resistant version features dual mechanical shutter system to help prevent insertion of foreign objects.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

## Specifications

### General Info

|                    |                          |                     |                         |
|--------------------|--------------------------|---------------------|-------------------------|
| Product Line       | Pass & Seymour           | Color               | Light Almond            |
| Finish             | Matte                    | UPC Number          | 785007006148            |
| Country Of Origin  | Mexico                   | Features            | Combination             |
| Switch Type        | Toggle                   | Number of Switches  | 2                       |
| Application Sector | Hospitality, Residential | Wall Plate Included | No                      |
| Standard           | UL20                     | Warranty Type       | 1-Year Limited Warranty |
| Type               | Combination, Switch      |                     |                         |

### Dimensions

|                                       |                                                                   |                          |                          |
|---------------------------------------|-------------------------------------------------------------------|--------------------------|--------------------------|
| Product Width US                      | 1.32 in                                                           | Product Depth US         | 0.94 in                  |
| Product Height US                     | 4.06 in                                                           |                          |                          |
| Listing Agencies / 3rd Party Agencies |                                                                   |                          |                          |
| cULus ListingNumber                   | 140597                                                            | cULus Listed             | Yes                      |
| Technical Information                 |                                                                   |                          |                          |
| Load Rating                           | 15 A @ 120/277 VAC                                                | Contact Configuration    | N-0                      |
| Operating Cycles                      | 30000                                                             | Connection Location      | Side Only                |
| Terminal Accommodation                | #14 AWG - #12 AWG                                                 | Number of Gangs          | 1                        |
| Throw Type                            | Single Throw                                                      | Amperage                 | 15 A                     |
| Number of Poles                       | 3-Way                                                             | Requires Neutral Wire    | Yes                      |
| Indoor/Outdoor                        | Indoor                                                            | Mounting Type            | Wall Box                 |
| Wire Connection Type                  | Screw Terminals                                                   | Voltage                  | 120 VAC, 277 VAC         |
| Load Type                             | CFL, Fluorescent, Halogen,<br>Incandescent, LED, Universal, Xenon | Environmental Conditions | Flammability: UL94<br>V2 |