

Single-Pole, Double Combination Switch, 15A, 120/277V, With Ground, Ivory.



## Features & Benefits

Easily accessible break-off separate or common feed.

Long-life red neon lamp in pilot light rated 1/25 Watt, 125V.

Side wire #12 and #14 AWG.

Two devices fit into the space of one.

Grounding combination devices meet NEC Tamper-resistant version features dual mechanical shutter system to help prevent insertion of foreign objects.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

## Specifications

### General Info

|                    |                                       |                     |                         |
|--------------------|---------------------------------------|---------------------|-------------------------|
| Product Line       | Pass & Seymour                        | Color               | Brown                   |
| Finish             | Satin                                 | UPC Number          | 785007690026            |
| Country Of Origin  | Mexico                                | Features            | Combination             |
| Switch Type        | Toggle                                | Number of Switches  | 2                       |
| Application Sector | Hospitality, Residential              | Wall Plate Included | No                      |
| Standard           | UL20                                  | Warranty Type       | 1-Year Limited Warranty |
| Type               | Combination, Switch, Tamper-Resistant |                     |                         |

Dimensions

|                   |         |                  |         |
|-------------------|---------|------------------|---------|
| Product Width US  | 1.32 in | Product Depth US | 0.94 in |
| Product Height US | 4.06 in |                  |         |

Listing Agencies / 3rd Party Agencies

|                     |        |              |     |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | 140597 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

Technical Information

|                        |                                                                |                          |                       |
|------------------------|----------------------------------------------------------------|--------------------------|-----------------------|
| Load Rating            | 15 A @ 120/277 VAC                                             | Contact Configuration    | N-0                   |
| Operating Cycles       | 30000                                                          | Connection Location      | Side Only             |
| Terminal Accommodation | #14 AWG - #12 AWG                                              | Number of Gangs          | 1                     |
| Throw Type             | Single Throw                                                   | Amperage                 | 15 A                  |
| Number of Poles        | Single Pole                                                    | Requires Neutral Wire    | Yes                   |
| Indoor/Outdoor         | Indoor                                                         | Mounting Type            | Wall Box              |
| Wire Connection Type   | Screw Terminals                                                | Voltage                  | 120 VAC, 277 VAC      |
| Load Type              | CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon | Environmental Conditions | Flammability: UL94 V2 |