

## radiant Collection radiant® GFCI USB Outlet with SafeLock® Protection, Type A/C, 15A, Tamper-Resistant, Brown Part No. 1597TRUSBAC



Enjoy superior safety and the convenience of built-in USB charging, in a first-of-its-kind outlet! Perfect for adding modern connectivity anywhere, including areas of the home where ground fault protection is required (kitchens, bathrooms, laundry rooms, etc). This outlet makes it easy to see and reset electrical trips right where they happen, while also providing two USB connections for keeping phones or tablets charged, no bulky adapter required. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately.

## Features & Benefits

outlet for easier charging, anywhere

ports for convenient charging. Shares 2.0A charging capacity between both ports

Equipped with proven SafeLock™ feature which disconnects power to the outlet if any critical components are damaged for added protection

for easier access.

Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection.

First outlet of its kind to add USB connection to a GFCI Provides reliable ground fault protection with a trip indicator light and reset button on the outlet for easy, accessible troubleshooting

Includes traditional power outlets and two USB Type-A Self-tests every three seconds, ensuring continuous ground fault protection for greater safety. Additionally, in case of test failure, the indicator light (red LED) will flash to signal there is an issue and the outlet should be replaced

> Protect children using a patented ""invisi-shutter"" system to prevent the insertion of foreign objects while maintaining a discreet, invisible effect. Meets NEC® Tamper-Resistant requirements

Installs quickly thanks to a redesigned side wire cavity. Can provide ground fault protection to downstream outlets through feed-thru wiring.

## **Specifications**

## General Info

| Product Line       | Pass & Seymour                                  | Color                 | Brown   |
|--------------------|---|-----------------------|---|
| Finish             | Matte   | UPC Number            | 785007309973  |
| Country Of Origin  | China   | Number of Receptacles | 2   |
| Features           | USB-A Charging, USB-C Charging                  | Outlet Type           | GFCI, Self-Test, Tamper-<br>Resistant, USB-Charging |
| Application Sector | Commercial, Multi-Dwelling Unit,<br>Residential | Wall Plate Included   | No  |
| Warranty Type      | 1-Year Limited Warranty                         |                       |   |

| Additional Information  RoHS Compliant Yes  Technical Information  Is Tamper-Resistant Yes Connection Location Back and Side  USB Amperage 2 A Number of USBs 2  Number of Wires 3 Number of Gangs 1  Amperage 15 A Number of Poles Double Pole  Is Weather Resistant No Indoor/Outdoor Indoor  Wattage 1875 W NEMA Configuration Code 5-15R   |                      |                    |                         |  |
|--|----------------------|--------------------|-------------------------|--|
| Product Height US 4.2 in  Listing Agencies / 3rd Party Agencies  CSA Listed Yes cULus ListingNumber E140596  cULus Listed Yes CSA File Number S5  Additional Information  RoHS Compliant Yes  Technical Information  Is Tamper-Resistant Yes Connection Location Back and Side  USB Amperage 2 A Number of USBs 2  Number of Wires 3 Number of Gangs 1  Amperage 15 A Number of Potes Double Pole  Is Weather Resistant No Indoor/Outdoor Indoor  Wattage 1875 W NEMA Configuration Code 5-15R  Mounting Type Box Wire Connection Type Internal Pressure Plates, Screw Terminals   | Dimensions           |                    |                         |  |
| Listing Agencies / 3rd Party Agencies  CSA Listed Yes cULus ListingNumber E140596  cULus Listed Yes CSA File Number S5  Additional Information  RoHS Compliant Yes  Technical Information  Is Tamper-Resistant Yes Connection Location Back and Side  USB Amperage 2 A Number of USBs 2  Number of Wires 3 Number of Gangs 1  Amperage 15 A Number of Poles Double Pole  Is Weather Resistant No Indoor/Outdoor Indoor  Wattage 1875 W NEMA Configuration Code 5-15R  Mounting Type Box Wire Connection Type Internal Pressure Plates, Screw Terminals   | Product Width US     | 1.73 in            | Product Depth US        | 1.03 in                                      |
| CSA Listed Yes CULus ListingNumber E140596  CULus Listed Yes CSA File Number CSA C22.2 No. 223, CSA C22.2 No. 55  Additional Information  RoHS Compliant Yes  Technical Information  Is Tamper-Resistant Yes Connection Location Back and Side  USB Amperage 2 A Number of USBs 2  Number of Wires 3 Number of Gangs 1  Amperage 15 A Number of Poles Double Pole  Is Weather Resistant No Indoor/Outdoor Indoor  Wattage 1875 W NEMA Configuration Code 5-15R  Mounting Type Box Wire Connection Type Internal Pressure Plates, Screw Terminals   | Product Height US    | 4.2 in             |                         |  |
| CSA C22.2 No. 223, CSA C22.2 No. | Listing Agencies / 3 | Brd Party Agencies |                         |  |
| Additional Information  RoHS Compliant Yes  Technical Information  Is Tamper-Resistant Yes Connection Location Back and Side  USB Amperage 2 A Number of USBs 2  Number of Wires 3 Number of Gangs 1  Amperage 15 A Number of Poles Double Pole  Is Weather Resistant No Indoor/Outdoor Indoor  Wattage 1875 W NEMA Configuration Code 5-15R  Mounting Type Box Wire Connection Type Internal Pressure Plates, Screw Terminals   | CSA Listed           | Yes                | cULus ListingNumber     | E140596                                      |
| Technical Information  Is Tamper-Resistant Yes Connection Location Back and Side  USB Amperage 2 A Number of USBs 2  Number of Wires 3 Number of Gangs 1  Amperage 15 A Number of Poles Double Pole  Is Weather Resistant No Indoor/Outdoor Indoor  Wattage 1875 W NEMA Configuration Code 5-15R  Mounting Type Box Wire Connection Type Internal Pressure Plates, Screw Terminals   | cULus Listed         | Yes                | CSA File Number         | CSA C22.2 No. 223, CSA C22.2 No.<br>55       |
| Technical Information  Is Tamper-Resistant Yes Connection Location Back and Side  USB Amperage 2 A Number of USBs 2  Number of Wires 3 Number of Gangs 1  Amperage 15 A Number of Poles Double Pole  Is Weather Resistant No Indoor/Outdoor Indoor  Wattage 1875 W NEMA Configuration Code 5-15R  Mounting Type Box Wire Connection Type Internal Pressure Plates, Screw Terminals   | Additional Informat  | ion                |                         |  |
| Is Tamper-Resistant Yes Connection Location Back and Side  USB Amperage 2 A Number of USBs 2  Number of Wires 3 Number of Gangs 1  Amperage 15 A Number of Poles Double Pole  Is Weather Resistant No Indoor/Outdoor Indoor  Wattage 1875 W NEMA Configuration Code 5-15R  Mounting Type Box Wire Connection Type Internal Pressure Plates, Screw Terminals  | RoHS Compliant       | Yes                |                         |  |
| USB Amperage 2 A Number of USBs 2  Number of Wires 3 Number of Gangs 1  Amperage 15 A Number of Poles Double Pole  Is Weather Resistant No Indoor/Outdoor Indoor  Wattage 1875 W NEMA Configuration Code 5-15R  Mounting Type Box Wire Connection Type Internal Pressure Plates, Screw Terminals   | Technical Informati  | on                 |                         |  |
| Number of Wires 3 Number of Gangs 1  Amperage 15 A Number of Poles Double Pole  Is Weather Resistant No Indoor/Outdoor Indoor  Wattage 1875 W NEMA Configuration Code 5-15R  Mounting Type Box Wire Connection Type Internal Pressure Plates, Screw Terminals  | Is Tamper-Resistant  | Yes                | Connection Location     | Back and Side                                |
| Amperage 15 A Number of Poles Double Pole  Is Weather Resistant No Indoor/Outdoor Indoor  Wattage 1875 W NEMA Configuration Code 5-15R  Mounting Type Box Wire Connection Type Internal Pressure Plates, Screw Terminals   | USB Amperage         | 2 A                | Number of USBs          | 2  |
| Is Weather Resistant No Indoor/Outdoor Indoor  Wattage 1875 W NEMA Configuration Code 5-15R  Mounting Type Box Wire Connection Type Internal Pressure Plates, Screw Terminals  | Number of Wires      | 3                  | Number of Gangs         | 1  |
| Wattage 1875 W NEMA Configuration Code 5-15R  Mounting Type Box Wire Connection Type Internal Pressure Plates, Screw Terminals   | Amperage             | 15 A               | Number of Poles         | Double Pole                                  |
| Mounting Type Box Wire Connection Type Box Terminals   | Is Weather Resistant | No                 | Indoor/Outdoor          | Indoor                                       |
| Mounting Type Box Wire Connection Type Terminals   | Wattage              | 1875 W             | NEMA Configuration Code | 5-15R  |
| Voltage 125.0 V  | Mounting Type        | Вох                | Wire Connection Type    | Internal Pressure Plates, Screw<br>Terminals |
|  | Voltage              | 125.0 V            |                         |  |