

---

PRODUCT SHEET

# **OCAL-BLUE<sup>®</sup> double-coat UL listed Type 4X form 8 conduit bodies**



# OCAL-BLUE® double-coat UL listed Type 4X form 8 conduit bodies

Ideal for washdown applications — UL listed Type 4X and NEMA 4X



01



02

01 3/4" T form 8 conduit body and cover

02 2" C form 8 conduit body and cover

## Innovative updates

For the conduit system that has to stand up to a corrosive environment, the OCAL-BLUE Type 4X form 8 conduit body meets the challenge. The key is in the cover—Ocal takes a cast cover and then injection molds a PVC coating around it with an integral O-ring seal.

There's no need for tools or gaskets. To meet the harsh requirements of the UL Type 4X listing, you need only hand-tighten the stainless steel encapsulated screws to 15 in-lbs of torque.

Ideal for providing corrosion-resistant performance in washdown and other tough applications, OCAL-BLUE Type 4X form 8 PVC-coated cast-iron conduit bodies are available in sizes up to 2 inches. Look for the blue to know it's a high-quality ABB product.

## Applications

- Food and beverage processing
- Water and wastewater treatment
- Petrochemical refining and processing
- Bridges, tunnels and other transportation infrastructure
- Coal mine cleaning operations

## Standards/certifications

- Specifications
  - UL listed Type 4X
  - NEMA 4X
- Standards
  - UL 514A
  - NEMA 250
- Listings
  - UL listed

## Features and benefits

- UL listed Type 4X and NEMA 4X rating for excellent protection in washdown areas, as well as harsh outdoor environments exposed to moisture, rain, ice or snow
- Double coated for superior corrosion protection — bodies and covers coated inside and out with 0.002" (2 mils) blue urethane, then exterior coated with a minimum of 0.040" (40 mils) PVC
- PVC coating in your choice of blue, gray or white — custom colors available
- Conduit bodies ship complete (PVC-coated cast-iron conduit body comes with mated cast-iron cover, injection molded with an integral O-ring seal and stainless steel encapsulated screws)
- Covers also sold separately for replacement

### UL Type 4X form 8 conduit body with covers



#### Size (in. and metric size designator\*)

	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
<b>Shape</b>	<b>16</b>	<b>21</b>	<b>27</b>	<b>35</b>	<b>41</b>	<b>53</b>
C	C18-4X- <u>  </u>	C28-4X- <u>  </u>	C38-4X- <u>  </u>	C448-4X- <u>  </u>	C58-4X- <u>  </u>	C68-4X- <u>  </u>
LB	LB18-4X- <u>  </u>	LB28-4X- <u>  </u>	LB38-4X- <u>  </u>	LB448-4X- <u>  </u>	LB58-4X- <u>  </u>	LB68-4X- <u>  </u>
LL	LL18-4X- <u>  </u>	LL28-4X- <u>  </u>	LL38-4X- <u>  </u>	LL448-4X- <u>  </u>	LL58-4X- <u>  </u>	LL68-4X- <u>  </u>
LR	LR18-4X- <u>  </u>	LR28-4X- <u>  </u>	LR38-4X- <u>  </u>	LR448-4X- <u>  </u>	LR58-4X- <u>  </u>	LR68-4X- <u>  </u>
T	T18-4X- <u>  </u>	T28-4X- <u>  </u>	T38-4X- <u>  </u>	T448-4X- <u>  </u>	T58-4X- <u>  </u>	T68-4X- <u>  </u>
TB	TB18-4X- <u>  </u>	TB28-4X- <u>  </u>	TB38-4X- <u>  </u>	TB448-4X- <u>  </u>	TB58-4X- <u>  </u>	TB68-4X- <u>  </u>
X	X18-4X- <u>  </u>	X28-4X- <u>  </u>	X38-4X- <u>  </u>	X448-4X- <u>  </u>	X58-4X- <u>  </u>	X68-4X- <u>  </u>

### UL Type 4X form 8 replacement covers



#### Size (in. and metric size designator\*)

	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
<b>Cover</b>	<b>160F-4X-<u>  </u></b>	<b>280F-4X-<u>  </u></b>	<b>380F-4X-<u>  </u></b>	<b>480F-4X-<u>  </u></b>	<b>580F-4X-<u>  </u></b>	<b>680F-4X-<u>  </u></b>

\* Metric size designator (ANSI C80.1-1994)

To complete catalog number, add suffix for color of PVC coating: G = gray, W = white, B = blue.

Contact your ABB representative about custom colors.

**ABB Installation Products Inc.**  
Electrification Products Division  
860 Ridge Lake Blvd.  
Memphis, TN 38120

[tnb.abb.com](http://tnb.abb.com)

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB Inc.  
Copyright© 2018 ABB  
All rights reserved