

Project Info:	Type:
Job Ref:	Catalog Number:
Approvals:	Date:

2119 Specification Grade 1/2" Conduit Mount Die Cast Zinc.



APPLICATIONS

- Parking lot lighting.
- Building perimeter lighting.
- Outdoor Signage.

FEATURES

- **Sensor:** Conformal coated cadmium sulphide photocell resists effects of moisture and airborne contaminants. Photocell responds to the light spectrum near to that of a human eye.
- **Operation:** Delay of up to two minutes to prevent false switching due to light from passing vehicles, lightning, etc.
- **Standards:** Meets ANSI/UL773A.
- **Housing:** Die cast aluminum housing and base. Gasketed for weather protection.

SPECIFICATIONS

- **Voltage:** 120/208-277.
- **Tungsten:** 2000W/3470-4620W.
- **Ballast:** 1800VA/2080-2770VA.
- **LED:** 600VA/1040-1385VA.
- **ON/OFF:** Turn ON is 1 to 5fc, Turn OFF is 3 to 15fc, without the slide in position. ON/OFF adjustment is easily made by moving a slide cover. No tools required.
- **Time Delay:** On and Off.
- **Cell:** Cadmium sulphide, epoxy conformal coated 1/2" diameter.
- **Power Consumption:** Averages under 1 watt
- **Temperature Range:** -40 °F to +140 °F (-40 °C to +60 °C).
- **Fail Mode:** ON.



2119A
1/2" Conduit Mount Specification Grade, Die Cast Aluminum

REGULATORY LISTINGS

- ANSI
- UL773A

LIMITED WARRANTY

- 5-year manufacturer's warranty