

# EASY-WRAP™

## Electrical Tape

### Friction, Electrical Filler & Silicone Rubber Tape

EWFT, EWEF, EWSR Series



#### SPECIFICATIONS

- UL Listed and CSA (EWFT).
- **Temperature Rating (EWSR):** -53.8 °C to 204.4 (-65 °F to 400 °F).
- **APPLICATIONS (EWSR):** For use on applications up to 69 KV..  
Meets MIL-A-A-59163.

#### FEATURES

##### Friction Tape (EWFT)

- Cloth construction offers strong mechanical protection against abrasion and penetration of cable, splices and wire.
- Coated on both sides with a rubber adhesive for adhesion to all types of surfaces.

##### Electrical Filler Tape (EWEF)

- Butyl based insulation is 1/8" thick for build-up.
- Easy to mold around irregular shapes.
- Self-amalgamates into solid flexible mass.
- Will not corrode copper or aluminum and highly resistant to moisture.
- Rated for applications up to 5 KV.

##### Silicone Rubber Tape - 69 KV (EWSR)

- Self-bonding silicone rubber tape adheres to itself when wrapped under tension and fuses to form a homogeneous mass within 24 hours at room temperature or four hours at 176.6 °C (350 °F).
- No adhesive required; tape leaves no residue.
- Excellent dielectric properties.
- Waterproof and chemical resistant.
- Triangular configuration.



| CAT. NO.   | FIG. NO. | COLOR | LENGTH (FT.) | WIDTH (IN.) | THICKNESS (IN.) | STD. CTN. QTY. |
|------------|----------|-------|--------------|-------------|-----------------|----------------|
| EWFT157560 | 1        | Black | 60           | 0.750       | 0.015           | 1              |
| EWEF12155  | 2        | Black | 5            | 1.500       | 0.125           | 1              |
| EWSR121030 | 3        | Red   | 30           | 1.000       | 0.120           | 1              |