



SPECIFICATIONS

- UL Listed and CSA (EWRT).
- **Rubber Splicing Temperature Rating:** Dielectric strength 490 Volts per mil.
- Meets HH-553C Grade B and ASTM D-119; UL 510 listing #2C58.

FEATURES

Rubber Splicing (EWRT)

- High quality unvulcanized rubber that will bond quickly to itself to form a solid mass of watertight protection.
- Self-fusing with liner.
- Can be used as primary insulation for electrical wires and cable splices up to 600 volts.
- Conforms to irregular shapes and is flexible to withstand expansion and contraction.
- Highly resistant to salt water, steam, oils, detergents and other chemicals.

Harness Wrap (EWWH)

- A 5 mil PVC film, coated with a rubber adhesive for high elongation and exceptional adherence.
- Excellent conformability to the wiring harness and matte finish.

Duct Tape (EWDT)

- Superior cloth duct tapes, designed to meet all industry demands and applications.
- Uniform MD/CD tear properties.



CAT. NO.	FIG. NO.	COLOR	TENSILE (IN/LBS.)	LENGTH (FT.)	WIDTH (IN.)	THICKNESS (IN)	STD. CTN. QTY.
EWRT3022-.75	1	Black	—	22	0.750	0.030	1
EWRT3022-1.5	1	Black	—	22	1.500	0.030	1
EWRT3022-2	1	Black	—	22	2.000	0.030	1
EWWH5060	2	Black	—	60	0.750	0.005	1
EWDT-8	3	Silver	18	55	2.000	0.314	1