

High Temperature Spade, Ring, Piggyback & Disconnect HT SERIES

FEATURES

UN-INSULATED:

Spade style terminal, Nickel plated copper, brazed seam, 900 °F

UN-INSULATED:

Ring style terminal, Nickel plated copper, brazed seam, 900 °F

UN-INSULATED:

Turned up edges give this spade more safety and reliability.

UN-INSULATED:

Male disconnect

UN-INSULATED:

Female flag style terminal

UN-INSULATED:

Similar tongue style to a spade, block spades have longer, flatter sides designed for use in terminal blocks.

Female quick disconnect with brazed seam, 600V, 105 °C.



STYLE	INSULATION TYPE	WIRE RANGE	STUD SIZE	CERTIFICATION VARIANCE
Spade	Un-insulated	12-10	#10	
Ring	Un-insulated	22-18	#10	UL
Ring	Un-insulated	22-18	#6	NON-UL
Ring	Un-insulated	22-18	#8	UL
Ring	Un-insulated	16-14	#10	UL
Ring	Un-insulated	16-14	#6	UL
Ring	Un-insulated	16-14	#8	UL
Ring	Un-insulated	12-10	1/4	NON-UL
Ring	Un-insulated	12-10	#10	UL
Ring	Un-insulated	12-10	#8	NON-UL
Piggyback	Un-insulated	16-14	0.250	
Disconnect Male	Un-insulated	12-10	0.250	
Disconnect Female Flag	Un-insulated	16-14	0.250	
Disconnect Female Flag	Un-insulated	12-10	0.250	
Disconnect Female	Un-insulated	16-14	0.250	
Disconnect Female	Un-insulated	12-10	0.250	
Disconnect Female	Un-insulated	8	0.250	



		"S" PACKS		PRO PACKS		STD PACKS		BULK PACKS	
L (IN)	W (IN)	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY
0.499	0.384	HTS12-10-S	15	—	—	—	---	HTS12-10-BULK	1000
0.443	0.325	—	—	—	—	HTR22-10	100	HTR22-10-BULK	1000
0.443	0.270	—	—	—	—	HTR22-6	100	HTR22-6-BULK	1000
0.411	0.270	—	—	—	—	HTR22-8	100	HTR22-8-BULK	1000
0.450	0.384	—	—	HTR16-10-P	100	HTR16-10	100	HTR16-10-BULK	1000
0.470	0.345	—	—	—	—	HTR16-6	100	HTR16-6-BULK	1000
0.444	0.390	—	—	—	—	HTR16-8	100	HTR16-8-BULK	1000
0.616	0.482	—	—	—	—	HTR12-14	50	HTR12-14-BULK	1000
0.530	0.384	—	—	HTR12-10-P	60	HTR12-10	50	HTR12-10-BULK	1000
0.530	0.384	—	—	—	—	HTR12-8	50	HTR12-8-BULK	1000
0.625	0.291	—	—	—	—	HTP16-250-3	---	HTP16-250-3-BULK	1000
0.685	0.250	—	—	—	—	HTM12-250-3	50	HTM12-250-3-BULK	1000
0.506	0.312	—	—	HTSF16-250-3-P	60	HTSF16-250-3	60	HTSF16-250-3-BULK	1000
0.587	0.294	—	—	HTSF12-250-3-P	50	HTSF12-250-3	50	HTSF12-250-3-BULK	1000
0.500	0.250	HTF16-250-3-S	15	HTF16-250-3-P	60	HTF16-250-3	50	HTF16-250-3-BULK	1000
0.690	0.304	HTF12-250-3-S	15	—	—	---	---	HTF12-250-3-BULK	500
0.715	0.304	—	—	HTF8-250-3-P	—	HTF8-250-3	25	HTF8-250-3-BULK	1000