

EASY-WRAP™

Electrical Tape

Friction, Electrical Filler & Silicone Rubber Tape

EWFT, EWEF, EWSR Series



SPECIFICATIONS

- UL Listed and CSA (EWFT).
- **Temperature Rating (EWSR):** -53.8 °C to 204.4 (-65 °F to 400 °F).
- **APPLICATIONS (EWSR):** For use on applications up to 69 KV..
Meets MIL-A-A-59163.

FEATURES

Friction Tape (EWFT)

- Cloth construction offers strong mechanical protection against abrasion and penetration of cable, splices and wire.
- Coated on both sides with a rubber adhesive for adhesion to all types of surfaces.

Electrical Filler Tape (EWEF)

- Butyl based insulation is 1/8" thick for build-up.
- Easy to mold around irregular shapes.
- Self-amalgamates into solid flexible mass.
- Will not corrode copper or aluminum and highly resistant to moisture.
- Rated for applications up to 5 KV.

Silicone Rubber Tape - 69 KV (EWSR)

- Self-bonding silicone rubber tape adheres to itself when wrapped under tension and fuses to form a homogeneous mass within 24 hours at room temperature or four hours at 176.6 °C (350 °F).
- No adhesive required; tape leaves no residue.
- Excellent dielectric properties.
- Waterproof and chemical resistant.
- Triangular configuration.



CAT. NO.	FIG. NO.	COLOR	LENGTH (FT.)	WIDTH (IN.)	THICKNESS (IN.)	STD. CTN. QTY.
EWFT157560	1	Black	60	0.750	0.015	1
EWEF12155	2	Black	5	1.500	0.125	1
EWSR121030	3	Red	30	1.000	0.120	1