ANDUIT<sup>®</sup> ELECTRICAL SOLUTIONS



B1.

**Cable Ties** 

B2. Cable Accessories

B3. Stainless Steel Ties

> C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion

Protection

C4. Cable Management

> D1. Terminals

D2. Power Connectors

D3.

Grounding

Connectors


E1. Labeling Systems


> E2. Labels

E3. Pre-Printed & Write-On Markers

## Pan-Way<sup>®</sup> Twin-70 Surface Raceway System

- UL and CSA rated 600 V; meets UL 5A and CSA C22.2 No. 62.1-03 standards; FT4 rated
- Separate channels allow independent access to power and communication cabling throughout the entire system
- Transitions to Panduit T-70, T-45, and LD profile raceway
- Compatible with NEMA standard 70mm faceplates or Pan-Way® Classic Series Snap-On Faceplates
- Tamper resistant
- · Supplied with pre-punched mounting holes





Part Number	Part Description	Raceway Size	Color‡	Length (Ft.)	Std. Ctn. Qty.
Twin-70 Raceway Base					
T702BIW8	Twin-70 raceway base in 8' and 10' lengths. Supplied with pre-punched mounting holes.	7.23" x 1.77" (184.0mm x 45.0mm)	Off White	8	24
T702BIW10				10	30
T-70/TG-70/Twin-70 Raceway Cover					
T70CIW8	T-70, TG-70, or Twin-70 raceway cover in 8' and 10' lengths.		Off White	8	96
T70CIW10				10	120
T-70/Twin-70 Raceway Divider Wall					
T70DW8	T-70/Twin-70 raceway divider wall. Snaps onto rails in T-70/Twin-70 raceway base to create separate channels. Must use wire retainers to ensure channel separation per UL/CSA. Available in 8' and 10' lengths.		Gray	8	96
T70DW10				10	120

‡ For other colors replace IW (Off White) with EI (Electric Ivory) or WH (White).

2' of cover needed for every 1' of Twin-70 base.

Order number of feet required in multiples of standard carton quantity.

T70DW

T702B

T70C



E5. Lockout/ Tagout & Safety Solutions

> F. Index