

A.  
System  
Overview

B1.  
Cable Ties

B2.  
Cable  
Accessories

B3.  
Stainless  
Steel Ties

C1.  
Wiring  
Duct

C2.  
Surface  
Raceway

C3.  
Abrasion  
Protection

C4.  
Cable  
Management

D1.  
Terminals

D2.  
Power  
Connectors

D3.  
Grounding  
Connectors

E1.  
Labeling  
Systems

E2.  
Labels

E3.  
Pre-Printed  
& Write-On  
Markers

E4.  
Permanent  
Identification

E5.  
Lockout/  
Tagout/  
& Safety  
Solutions

F.  
Index




## Two-Hole, Straight Tongue, Two-Barrel Lug

**For Use with Copper Code Conductors**

### Type H2L-2N

- Allows for termination of two copper conductors
- Cast from high strength corrosion resistant copper alloy to provide premium electrical and mechanical performance
- Wide wire range-taking capability minimizes inventory requirements
- Internal pressure plate provides uniform clamping force on conductor for premium electrical performance
- Internal barrel serrations provide premium wire pull-out strength
- Inspection window to visually assure full conductor insertion
- Flat bottom allows for complete contact with mounting surface
- UL Listed for use up to 600 V and temperature rated 90°C
- Available with NEMA hole sizes and spacing



| Part Number  | Copper Conductor Size Range | Stud Hole Size (In.) | Stud Hole Spacing (In.) | Hex Key Size (In.) | Figure Dimensions (In.) |      |      |      |      | Std. Pkg. Qty. |
|--------------|-----------------------------|----------------------|-------------------------|--------------------|-------------------------|------|------|------|------|----------------|
|              |                             |                      |                         |                    | L                       | W    | H    | T    | P    |                |
| ◆ H2L4-2N-X  | #8 SOL – #4 STR             | 1/2                  | 1.75                    | **                 | 3.75                    | 1.25 | 0.76 | 0.19 | 3.00 | 10             |
| ◆ H2L8-2N-2  | #4 SOL – #1 STR             | 1/2                  | 1.75                    | 7/16               | 3.94                    | 1.38 | 0.92 | 0.22 | 3.00 | 2              |
| ◆ H2L13-2N-2 | #1 STR – 2/0 STR            | 1/2                  | 1.75                    | 9/16               | 4.00                    | 1.63 | 1.06 | 0.22 | 3.00 | 2              |
| ◆ H2L21-2N-2 | 2/0 STR – 4/0 STR           | 1/2                  | 1.75                    | 9/16               | 4.19                    | 1.88 | 1.34 | 0.31 | 3.00 | 2              |
| ◆ H2L30-2N-1 | 4/0 STR – 300 kcmil         | 1/2                  | 1.75                    | 5/8                | 4.38                    | 2.00 | 1.45 | 0.31 | 3.00 | 1              |

\*\*Uses slotted head set screw.  
◆NEMA hole sizes and spacing.




## Two-Hole, Straight Tongue, Two-Barrel, Tin-Plated Lug

**For Use with Copper Code Conductors**

### Type P2NLT

- Allows for termination of two copper conductors
- Cast from high strength corrosion resistant copper alloy to provide premium electrical and mechanical performance
- Tin-plated to inhibit corrosion
- Wide wire range-taking capability minimizes inventory requirements
- Internal barrel serrations provide premium wire pull-out strength
- Inspection window to visually assure full conductor insertion
- Plated steel set screw provides high strength, durable electrical contact
- Flat bottom allows for complete contact with mounting surface
- UL Listed for use up to 600 V and temperature rated 90°C
- Available with NEMA hole sizes and spacing



| Part Number   | Copper Conductor Size Range | Stud Hole Size (In.) | Stud Hole Spacing (In.) | Hex Key Size (In.) | Figure Dimensions (In.) |      |      |      |      | Std. Pkg. Qty. |
|---------------|-----------------------------|----------------------|-------------------------|--------------------|-------------------------|------|------|------|------|----------------|
|               |                             |                      |                         |                    | L                       | W    | H    | T    | P    |                |
| ◆ P2NLT-500-3 | #4 SOL – 500 kcmil          | 1/2                  | 1.75                    | 3/8                | 4.50                    | 2.50 | 1.47 | 0.38 | 3.00 | 3              |

◆NEMA hole sizes and spacing.