


A.  
System  
Overview



## Super-Grip® Cable Ties – Nylon 6.6

- For indoor use
- Designed to grip the bundle tightly to resist lateral movement of the tie once installed
- High strength allows the tie to withstand rough installation practices that occur in MRO and construction environments
- Thin, wide strap body provides flexibility enabling it to conform to bundle while maintaining tensile strength

- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation
- UL Listed for use in plenum or air handling spaces per NEC
- Complementary mounts available, see pages B2.7, B2.11, B2.13 and B2.21



C1.  
Wiring  
Duct

C2.  
Surface  
Raceway

C3.  
Abrasion  
Protection

C4.  
Cable  
Management

D1.  
Terminals

D2.  
Power  
Connectors

D3.  
Grounding  
Connectors

E1.  
Labeling  
Systems

E2.  
Labels

E3.  
Pre-Printed  
& Write-On  
Markers

E4.  
Permanent  
Identification

E5.  
Lockout/  
Tagout  
& Safety  
Solutions

F.  
Index

|                                           | Length |     | Width |     | Thickness |     | Max. Bundle Dia. |     | Min. Loop Tensile Strength |     | Recommended Installation Tool                          | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------------------------------------|--------|-----|-------|-----|-----------|-----|------------------|-----|----------------------------|-----|--------------------------------------------------------|----------------|----------------|
| Part Number                               | In.    | mm  | In.   | mm  | In.       | mm  | In.              | mm  | Lbs.                       | N   |                                                        |                |                |
| Miniature Cross Section – Plenum-Rated    |        |     |       |     |           |     |                  |     |                            |     |                                                        |                |                |
| SG100M-C                                  | 4.2    | 106 | .118  | 3.0 | .038      | 1.0 | .90              | 23  | 18                         | 80  | GTS, GTSL, GS2B, PTS, PPTS, STS2                       | 100            | 1000           |
| Intermediate Cross Section – Plenum-Rated |        |     |       |     |           |     |                  |     |                            |     |                                                        |                |                |
| SG150I-C                                  | 6.2    | 157 | .168  | 4.3 | .040      | 1.0 | 1.50             | 38  | 40                         | 178 | GTS, GTSL, GS2B, PTS, PPTS, STS2                       | 100            | 1000           |
| Standard Cross Section – Plenum-Rated     |        |     |       |     |           |     |                  |     |                            |     |                                                        |                |                |
| SG200S-C                                  | 8.3    | 211 | .225  | 5.7 | .046      | 1.2 | 2.00             | 51  | 50                         | 222 | GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2 | 100            | 1000           |
| SG250S-C                                  | 10.4   | 264 | .225  | 5.7 | .050      | 1.3 | 2.60             | 66  | 75                         | 334 |                                                        | 100            | 1000           |
| SG300S-C                                  | 12.4   | 315 | .225  | 5.7 | .050      | 1.3 | 3.20             | 81  | 75                         | 334 |                                                        | 100            | 1000           |
| SG370S-C                                  | 15.3   | 389 | .225  | 5.7 | .052      | 1.3 | 4.20             | 107 | 75                         | 334 |                                                        | 100            | 1000           |
| Light-Heavy Cross Section – Plenum-Rated  |        |     |       |     |           |     |                  |     |                            |     |                                                        |                |                |
| SG350LH-L                                 | 15.3   | 389 | .330  | 8.4 | .064      | 1.6 | 4.13             | 105 | 120                        | 534 | GTH, GS4H, GS4EH, PTH, STH2, ST3EH                     | 50             | 500            |
| Heavy Cross Section – Plenum-Rated        |        |     |       |     |           |     |                  |     |                            |     |                                                        |                |                |
| SG450H-L                                  | 18.6   | 471 | .380  | 9.7 | .068      | 1.7 | 5.20             | 132 | 175                        | 778 | GTH, GS4H, GS4EH, PTH, STH2, ST3EH                     | 50             | 500            |