ELECTRICAL SOLUTIONS

A. System **Overview**

Pan-Way® LD Surface Raceway System

- B1. **Cable Ties**
- For routing data and low voltage cabling • One-piece hinged design allows cables to be laid in
- Factory applied adhesive backing speeds installation
- FT4 rated
- Terminates using surface mount outlet box solutions or Panduit® Mini-Com® Surface Mount Boxes



B2. Cable Accessories

В3. Stainless **Steel Ties**

C1. Wiring

C3. Abrasion Protection

C4. Cable Management

> D1. Terminals

D2. Power Connectors

D3. Grounding Connectors

Labeling Systems

> E2. Labels


E3. Pre-Printed & Write-On Markers


E4. Permanent Identification

E5. Lockout/ Tagout & Safety Solutions


Index









LD5 Internal Area = .38 Sq. In.



LD10 Internal Area = 1.00 Sq. In.





LD5



LD₁₀

Part Number	Part Description	Raceway Size	Color‡	Length (Ft.)	Std. Ctn. Qty.
LD3 - Surface	e Raceway				
LD3IW6-A	One-piece latching surface raceway. Supplied with pre-applied adhesive backed tape. Available in 6', 8', and 10' lengths.	.77" x .46" (20.0mm x 12.0mm)	Off White	6	120
LD3IW8-A				8	160
LD3IW10-A				10	200
LD5 – Surface	Raceway				
LD5IW6-A	One-piece latching surface raceway. Supplied with pre-applied adhesive backed tape. Available in 6', 8', and 10' lengths.	1.01" x .58" (26.0mm x 15.0mm)	Off White	6	120
LD5IW8-A				8	160
LD5IW10-A				10	200
LD10 – Surfac	ce Raceway	ı		I	
LD10IW6-A	One-piece latching surface raceway. Supplied with pre-applied adhesive backed tape. Available in 6', 8', and 10' lengths.	1.51" x .94" (38.4mm x 24.0mm)	Off White	6	120
LD10IW8-A				8	160
LD10IW10-A				10	200

‡For other colors replace IW (Off White) with EI (Electric Ivory), IG (International Gray), or WH (White). Order number of feet required in multiples of standard length increments.