



## Mini-Com® In-Wall Fiber Spool

- Maintains 1" internal bend radius
- Cable entry/exit from rear, top, and bottom helps maintain external bend radius
- Designed for use with single or double gang wall board adapter
- Stores up to 12 meters of unjacketed fiber cable or two meters of jacketed fiber cable
- 3.65" (92.7mm) depth from rear of faceplate, not for use with in-wall boxes or in shallow walls



Standards: TIA/EIA-568-B requires a minimum 1 meter slack and a fiber spool for in-wall installations.

| Part Number   | Part Description                                                                                           | Color‡    | Std. Pkg. Qty. | Std. Ctn. Qty. |
|---------------|------------------------------------------------------------------------------------------------------------|-----------|----------------|----------------|
| <b>CFS2IW</b> | In-wall fiber spool for use with Mini-Com® Faceplates, Faceplate Frames, Inserts and Modular Patch Panels. | Off White | 1              | 10             |

‡For other colors replace suffix IW (Off White) with EI (Electric Ivory), WH (White), IG (International Gray), or BL (Black).



## Mini-Com® “GFCI” Decora Module Frames

- Mount behind any standard GFCI electrical faceplate
- Accept Mini-Com® Modules for STP and UTP, fiber optic, and audio/video, which snap in and out for easy moves, adds, and changes
- Optional adhesive labels available



CFG1IW



CFG2IW

| Part Number   | Part Description                             | Color‡    | Std. Pkg. Qty. | Std. Ctn. Qty. |
|---------------|----------------------------------------------|-----------|----------------|----------------|
| <b>CFG1IW</b> | Module frame accepts one Mini-Com® Module.   | Off White | 1              | 10             |
| <b>CFG2IW</b> | Module frame accepts two Mini-Com® Modules.  | Off White | 1              | 10             |
| <b>CFG4IW</b> | Module frame accepts four Mini-Com® Modules. | Off White | 1              | 10             |


‡For other colors replace suffix IW (Off White) with EI (Electric Ivory), WH (White), IG (International Gray), or BL (Black).

All frames include mounting screws.



CFG4IW

## Component Labels for Mini-Com® “GFCI” Decora Module Frames



### Suggested Label Solutions for TIA/EIA-606-A Compliance

| Frame Part Number | Laser/Ink Jet Desktop Printer Label | TDP43ME Thermal Transfer Desktop Printer Label | PanTher™ LS8E Hand-Held Printer Label | Cougar™ LS9 Hand-Held Printer Label |
|-------------------|-------------------------------------|------------------------------------------------|---------------------------------------|-------------------------------------|
| CFG1              | C061X030FJJ                         | C061X030YPT                                    | C061X030FJC                           | T031X000FJC-BK                      |
| CFG2              |                                     |                                                |                                       |                                     |
| CFG4              | C125X030FJJ                         | C125X030YPT                                    | C125X030FJC                           | T031X000FJC-BK                      |

For complete labeling solutions and product information, reference charts on pages O.1 – O.22 of SA-NCCB51.