



|                                                      |                                                                                                                                                            |
|------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                                             | High Conductivity<br>Seamless Copper Tube                                                                                                                  |
| Plating                                              | Electro-Tin                                                                                                                                                |
| Wire Size                                            | 350 STR/FLEX                                                                                                                                               |
| Wire Type                                            | Stranded Copper:<br>Class G, H, I, K, M,<br>Locomotive                                                                                                     |
| Wire Strip Length                                    | 1-3/8 in.                                                                                                                                                  |
| Stud Size                                            | 3/8 in.                                                                                                                                                    |
| UL Listed Wire<br>Connector                          | Yes, for applications up to 35kv.<br>Consult cable manufacturer for<br>voltage stress relief instructions<br>with applications greater than<br>2000 volts. |
| UL Temperature<br>Rating                             | 90° C                                                                                                                                                      |
| C.S.A Certified<br>Wire Connector                    | Yes                                                                                                                                                        |
| Panduit Color Code<br>on Barrel                      | BLUE                                                                                                                                                       |
| Panduit Die Index No.<br>on Barrel                   | P76                                                                                                                                                        |
| Alternate Industry<br>Die Index No. ( )<br>on Barrel | (19)                                                                                                                                                       |



LISTED  
Wire Connector



|     |      |     |     |             |       | <b>PANDUIT CORP.</b>                                         |                       | TINLEY PARK, ILLINOIS |
|-----|------|-----|-----|-------------|-------|--------------------------------------------------------------|-----------------------|-----------------------|
|     |      |     |     |             |       | LCDX350-38D-6<br>Copper Lug - Two-Hole, Standard Flex Barrel |                       |                       |
| 00  | 6/03 | SAC | SAC | RELEASED    | 10850 |                                                              |                       |                       |
| REV | DATE | BY  | CHK | DESCRIPTION | ECN   | SCALE                                                        | DRAWING NO / CAD FILE |                       |
|     |      |     |     |             |       | N/A                                                          | LCDX350-38D-CUST      |                       |