



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

|                                                |                                                                                                                                                |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                                       | High Conductivity Seamless Copper Tube                                                                                                         |
| Plating                                        | Electro-Tin                                                                                                                                    |
| Wire Size                                      | 6 STR/FLEX                                                                                                                                     |
| Wire Type                                      | Stranded Copper: Class B & C, Compact, Class G, H, I, K, M, Locomotive                                                                         |
| Wire Strip Length                              | 9/16 in.                                                                                                                                       |
| Stud Size                                      | 1/4 in.                                                                                                                                        |
| UL Listed Wire Connector                       | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. |
| UL Temperature Rating                          | 90° C                                                                                                                                          |
| C.S.A Certified Wire Connector                 | Yes                                                                                                                                            |
| Panduit Color Code on Barrel                   | BLUE                                                                                                                                           |
| Panduit Die Index No. on Barrel                | P24                                                                                                                                            |
| Alternate Industry Die Index No. ( ) on Barrel | (7)                                                                                                                                            |



LISTED  
Wire Connector



|     |      |      |      |                                      | PANDUIT CORP. TINLEY PARK, ILLINOIS                        |              |
|-----|------|------|------|--------------------------------------|------------------------------------------------------------|--------------|
|     |      |      |      |                                      | LCDX6-14B-L<br>Copper Lug - Two-Hole, Standard Flex Barrel |              |
| 01  | 7/03 | TLCO | TLCO | REMOVED PANDUIT FROM BARREL MARKINGS | 10918                                                      |              |
| REV | DATE | BY   | CHK  | DESCRIPTION                          | ECN                                                        | SCALE<br>N/A |
|     |      |      |      |                                      | DRAWING NO / CAD FILE<br>LCDX6-14B-CUST                    |              |