Mini-Com® Faceplate Frames and Inserts



specifications

Faceplate frames shall be available in single and double gang versions and shall accept a variety of inserts. Executive design faceplate frames shall have a curved appearance and include labels and label covers. Classic design faceplate frames shall have a flush appearance and include color matched mounting screws. Inserts shall be available in sloped, sloped shuttered, and flat versions, and accept all modules for increased design flexibility. Modules shall be accessible from the front for easy moves, adds, and changes.



technical information

Mounting options:	Faceplate frames are compatible with wall board adapters (MWBA1 and MWBA-2G); single or double junction boxes; raceway mounting brackets
Packaging:	Executive series faceplate frames include two labels, two label covers; all faceplate frames include 1" long #6-32 slotted pan head screws with non-threaded lead point

key features and benefits

Modular	Faceplate frames accept all Panduit Inserts; inserts accept all Mini-Com® Modules for design flexibility
Front access	Mini-Com® Modules are accessible from the front for easy moves, adds, and changes
Sloped versions	Provide additional bend radius control to protect cable
Shuttered versions	Integrated shuttered door keeps dust and debris out of unmated Mini-Com® Jack Modules
Identification	Executive series faceplate frames can be clearly identified with labels; classic series faceplate frames can be clearly identified with optional adhesive labels; sloped shuttered version available with label option; Mini-Com® Modules can be clearly identified with optional icons

applications

The combination of faceplate frames and inserts provide the design flexibility when installing connectivity in single or double gang junction boxes, wallboard adapters, and raceway mounting brackets. A variety of inserts enable front access to connectivity

for easy moves, adds, and changes. Sloped inserts are ideal for installations which require additional bend radius control and blank inserts allow for future growth. All inserts accept Mini-Com® Modules for copper, fiber, and audio/video applications.

Mini-Com® Faceplate Frames and Inserts

Executive Series Faceplate Frames

Single gang: CBE*Y
Double gang: CBE*-2GY

Classic Series Faceplate Frames

Single gang: CB*^
Double gang: CB*-2G^

1/2 Size Inserts

Sloped: CHS2*-X Sloped, shuttered: CHS1S*-X Sloped, shuttered: CHS2S*-X

Sloped, shuttered

with labels: CHLS2S*-X
Sloped, recessed: CHSRE2*-X
Flat: CHF2*-X
Blank: CHB2*-X

1/3 Size Inserts

Flat: CHF2M*-X Blank: CHB2M*-X

2/3 Size Inserts

Sloped, recessed: CHS2R2*-X

1/3 Size D-Subminiature Inserts

9-pin, female to

female coupler: CHD9C*Y

15-pin, female to

female coupler: CHD15HDC*Y

15-pin, DB connector

mounted to a

circuit board: CHD15HDSC*Y

RCA 1/3 Inserts

Red, green, blue: CHR3RGB* White, yellow, red: CHR3WYR*


*To designate color, add suffix IW (Off White), EI (Electric Ivory), IG (International Gray), AW (Arctic White), WH (White), or BL (Black).

^Frames CB** and CB**-2G require the following clearance when installing over a mud ring: CB**=2.80"x1.74" CB**-2G=2.83"x3.63"


Visit www.panduit.com for complete offering of copper, fiber, and audio/video modules.

Mini-Com® Faceplate Frames and Inserts

executive series faceplate frames classic series faceplate frames



inserts




Dimensions are in inches [Dimensions in brackets are metric].

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA Markham, Ontario cs-cdn@panduit.com Phone: 800.777.3300 PANDUIT EUROPE LTD. London, UK cs-emea@panduit.com Phone: 44.20.8601.7200 PANDUIT SINGAPORE PTE. LTD. Republic of Singapore cs-ap@panduit.com Phone: 65.6305.7575 PANDUIT JAPAN Tokyo, Japan cs-japan@panduit.com Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA Guadalajara, Mexico cs-la@panduit.com Phone: 52.33.3777.6000 PANDUIT AUSTRALIA PTY. LTD. Victoria, Australia cs-aus@panduit.com Phone: 61.3.9794.9020





Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com or by phone: 800.777.3300

© 2014 Panduit Corp. ALL RIGHTS RESERVED. OTSP38--WW-ENG Replaces WW-OTSP15 8/2014

