

Pan-Way® T-45 Surface Raceway System

specifications

T-45 non-metallic multi-channel, two-piece, hinged cover design surface raceway shall be used to route, protect, and conceal data, voice, video, fiber optic and power cabling. The raceway shall be listed as suitable for use in applications up to 600 volts between conductors by Underwriters Laboratories, Inc. per standard 5A, and by Canadian Standards Association, Inc. per 22.2 no. 62.1-03, when screw secured and installed per instructions. A full complement of fittings with a 1" minimum bend radius compliant with TIA/EIA-568-B, must be available as well as device brackets and junction boxes to install a variety of communication and electrical devices. Divider walls must be available to form separate channels in the multi-channel raceway. An offset box shall be available, with versions for "snap-on" as well as "screw mount" faceplates, for mounting the power receptacle or the data receptacles outside of the raceway channel. T-45 raceway will be manufactured from impact resistant material with flammability rating of V-0. T-45 raceway must be tamper resistant yet also allow access for moves, adds and changes. T-45 raceway finish shall be pure color and will resist scratches and dents and will not peel or corrode.



technical information

Material:	Rigid PVC
Flammability:	UL94V-0; FT4
Voltage rating:	UL-5A 600VAC; CSA C22.2 No. 62.1-03 600V
Approvals:	UL Listed 95425 (raceway); UL Listed E116129 (fittings)
NEC:	Article 388
Color:	IW (Off White), EI (Electrical Ivory), WH (White) available in 8 foot lengths only without adhesive
CSI spec form:	LP-CSISPEC-T45-1

key features and benefits

Unique size	Provides greater capacity in a smaller footprint allowing greater flexibility to match the raceway to the application.
1" bend radius control fittings	Meets TIA/EIA standard and many warranty requirements
Designer profile	Maintains the same aesthetically pleasing profile of Panduit® T-70, Twin-70 and TG-70 Raceway which allows all four systems to work together or independently
Multi-directional hinge	Easy access from either side of the raceway provides more convenience for moves, adds and changes; latch is tamper resistant which provides maximum security for communication cabling and maximum safety for power cabling
Multi-channel capable	Capable of routing both power and communication cabling in a single raceway
Multi-termination options	Ability to create many different configurations using in-line termination features, offset boxes or certain Pan-Way surface mount boxes.

applications

Pan-Way® T-45 Non-Metallic Surface Raceway is a multi-channel channel raceway which provides solutions for routing low voltage, fiber optic and/or power cabling along perimeter walls. T-45 Surface Raceway terminates using the T-45 Hinged Data

and Power Brackets, T-45 Offset Box and Pan-Way® Surface Mount Outlet Boxes and superior Pan-Way® Snap-On Faceplates. Fittings for T-45 are available to transition to Pan-Way® LD Series Raceways.

www.panduit.com

Pan-Way® T-45 Raceway

Raceway Base with adhesive	
8 feet:	T45BIW8-A
10 feet:	T45BIW10-A
Raceway Base without adhesive	
8 feet:	T45BIW8
10 feet:	T45BIW10
Raceway Cover	
8 feet:	T45CIW8
10 feet:	T45CIW10
Divider walls	
8 feet:	T45DW8
10 feet:	T45DW10

T-45 Raceway Fittings

Cover coupler fitting:	T45CCIW-X
Outside corner fitting:	T45OCIW
Inside corner fitting:	T45ICIW
Right angle fitting:	T45RAIW
End cap fitting:	T45ECIW
Entrance end fitting:	T45EEIW
Bend radius control fitting:	T45TRI
Reducer fitting:	T45RLDIW
Tee fitting:	T45TIW
Insert for tee fitting:	T45TD


T-45 Raceway Accessories

Hinged data bracket:	T45HDBIW
Wire retainer:	T45WR-X
Workstation Outlet Center™ Offset box:	T45WCIW
Workstation Outlet Center™ Offset box:	T45WC2IW
Electrical bracket and box for duplex outlets:	T45HEBIW
Electrical bracket and box for rectangular outlets:	T45HEGBIW

All parts listed in Off White (IW) color. To order other colors substitute Electrical Ivory (EI) or White (WH).

Pan-Way® T-45 Surface Raceway System

Wire Fill



T-45
Internal Area = 2.12 Sq. In.

Raceway Type and Configuration	Fill Area (in ²)	Electrical Cables			Data Grade Cables												Coax Cables				Fiber Optic Cable					
		14 AWG	12 AWG	10 AWG	24 AWG		24 AWG		24 AWG		24 AWG		24 AWG		24 AWG		24 AWG		24 AWG		24 AWG		24 AWG			
		THHN/THWN/T90			Cat. 5e - Plenum	Cat. 5e - Riser	Cat. 6		Cat. 6A		Cat. 6A		Cat. 6A		Cat. 6A (SD)		RG6		RG59/u		2 Strand					
		0.111	0.130	0.164	DIA = 0.193	DIA = 0.225	DIA = 0.240		DIA = 0.289		DIA = 0.300		DIA = 0.330		DIA = 0.240		DIA = 0.275		DIA = 0.242		DIA = 0.175					
		FILL			FILL	FILL	FILL		FILL		FILL		FILL		FILL		FILL		FILL		FILL		FILL			
MAX	MAX	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX
(UL Temp Rise Test)			(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)	(40%)	(60%)
T-45: No Devices	2.13	36	27	25	29	43	21	32	18	28	12	19	12	18	9	14	18	28	14	21	18	27	35	53		
T-45: No Devices with wire retainer	1.72	36	27	25	23	35	17	25	15	22	10	15	9	14	8	12	15	22	11	17	14	22	28	42		
T-45: Power & data with wire retainer & divider wall (2 channels)	0.44	12	11	8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	1.20	-	-	-	16	24	12	18	10	15	7	10	6	10	5	8	10	15	8	12	10	15	19	29		
T-45: Power & data with wire retainer & two divider walls (3 channels)	0.44	12	11	8	6	9	4	6	3	5	2	4	2	3	2	3	3	5	2	4	3	5	7	10		
	0.68	-	-	-	9	13	6	10	6	9	4	6	3	5	3	4	6	9	4	6	5	8	11	16		
	0.44	-	-	-	6	9	4	6	3	5	2	4	2	3	2	3	3	5	2	4	3	5	7	10		
T-45: Power and data using the Workstation Outlet Center™ Offset Box	0.41	12	11	8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	1.06	-	-	-	14	21	10	15	9	14	6	9	5	8	4	7	9	14	7	10	9	13	17	26		
T-45: Data only using data bracket	2.00	-	-	-	27	41	20	30	17	26	12	18	11	16	9	14	17	26	13	20	17	26	33	49		
T-45 Power and Data using Hinged Data Bracket with Divider Insert	0.52	12	11	8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	1.20	-	-	-	16	24	12	18	10	15	7	10	6	10	5	8	10	15	8	12	10	15	19	29		
T-45: Power and Data Using Electrical Bracket and Box	0.22	9	7	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	0.50	-	-	-	6	10	5	7	4	6	3	4	2	4	2	3	4	6	3	5	4	6	8	12		

Pan-Way® T-45 Surface Raceway System

T-45 Raceway



T45B



T45C


Fittings and Accessories



T45CC**X



T450C




T451C



T45RA




T45EC




T45EE



T45TRI



T45RLD



T45TD



T45T



T45HDB



T45DW



T45WR-X



T45WC



T45WC2



T45HEB



T45HEGB

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA
Markham, Ontario
cs-cdn@panduit.com
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
cs-emea@panduit.com
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
cs-ap@panduit.com
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
cs-japan@panduit.com
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
cs-la@panduit.com
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
cs-aus@panduit.com
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com
or by phone: 800.777.3300

PANDUIT®

©2015 Panduit Corp.
ALL RIGHTS RESERVED.
SRSP24--WW-ENG
Replaces WW-SRSP08
1/2015