



Understanding the Label

IMPORTANT!: Determine the desired direction of cable **before** wiring the cap. The cap, in relation to the jack, **must** be kept consistent throughout the entire termination.




S/FTP


Individual foil pair screen
Conductors
Braid

**SF/UTP**


Overall foil screen
Conductors
Braid

**U/FTP**

Individual foil pair screen
Conductors
Drain wire




**F/UTP**

Overall foil screen
Conductors
Drain wire






Up Orientation

1




IMPORTANT!:
Be sure that strain relief is fully retracted before inserting cable.


2



3




Do not pre-arrange conductors.




Bend wires to ease inserting them into the cap.


4



5




Cable End 1 Shown



Cable End (1)




(OR)




Cable End (2)




6

Be sure cable is fully inserted into wire cap










Cable End 1 Shown






Up Orientation**7****T568B Wiring****Cable End 1****1.****Cable End 2****1.****2.****T568A Wiring**

T568A not shown on wire map label




**Termination side****Label side****Cable End 1****1.****2.****Cable End 2****1.****2.****8****9****Important!**
Maintain orientation of cap in relation to jack from previous steps.**10****11**

Down Orientation




IMPORTANT!
Be sure that strain relief is fully retracted before inserting cable.

2




Do not pre-arrange conductors.

3





Bend wires to ease inserting them into the cap.

4






Cable End 1 Shown

5




6

Be sure cable is fully inserted into wire cap





Cable End 1 Shown



Down Orientation


7

T568B Wiring




T568A Wiring


T568A not shown on wire map label




Cable End 1




Cable End 1




Cable End 2




Cable End 2



8




9





Important!
Maintain orientation of
cap in relation to jack
from previous steps.

10



11



REMOVAL STEPS**Notes:**

1. For specified performance, follow TIA/EIA 568-C installation guidelines.
2. Jack Modules can terminate 22-26 AWG solid data cable with 0.062" (1.57mm) maximum insulated conductor outside diameter.
3. Jack Modules may be re-terminated at least 20 times.
4. For technical and performance information, consult Panduit Technical Support.

As with all Wiring Accessories, the following statements apply:

1. Never install communications wiring during a lightning storm.
2. Never install communications wiring in wet locations unless the jack is specifically designed for use in wet locations.
3. Never touch uninsulated communications wiring or terminals unless the communication line has been disconnected at the network interface.
4. Use caution when installing or modifying communication wiring.

For Instructions in Local Languages
and Technical Support:

www.panduit.com/resources/install_maintain.asp

PANDUIT
www.panduit.com

E-mail:
techsupport@panduit.com

Phone:
866-405-6654