PHYSICAL INFRASTRUCTURE SYSTEMS

Copper **Systems**

C. Fiber **Optic** Systems

D. Power over Ethernet

E. Zone Cabling

Wireless

Outlets

Н. Media Distribution

Ι. **Physical** Infrastructure Management

J. Overhead & Underfloor Routing

> Surface Raceway

L. Cabinets, Racks & Cable Management

Grounding & Bonding

N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

Index

Mini-Com® 15-Pin High-Density D-Subminiature Module

- Field terminable module features 15-pin screw terminal
- · Dual module configuration allows it to be installed in Mini-Com® Faceplates (plastic and stainless steel)
- SVGA compatible
- Compatible with select Mini-Com® Modular Patch Panels, Faceplates, and Surface Mount Boxes



Part Number	Part Description	No. of Module Spaces	Color‡	Std. Pkg. Qty.	Ctn.
CMD15HDIWY	2-position module supplied with one 15-pin DB connector mounted to a printed circuit board; terminates on site.	2	Off White	1	10

‡For other colors replace suffix IW (Off White) with EI (Electric Ivory), WH (White), IG (International Gray), or BL (Black).

Mini-Com® Module Base for D-Subminiature Connectors

- · Accepts 9-pin or 15-pin high-density connector, male or female, solder or crimp type (connector not included)
- Compatible with select Mini-Com® Modular Patch Panels, Faceplates, and Surface Mount Boxes



Part Number	Part Description	No. of Module Spaces	Color‡	Std. Pkg. Qty.	Ctn.
CMDBIW-X	2-position module base which accepts 9-pin and 15-pin high density D-subminiature connectors.	2	Off White	10	100

‡For other colors replace suffix IW (Off White) with EI (Electric Ivory), WH (White), IG (International Gray), or BL (Black).

D-Subminiature Inserts

Used in audio and video applications

Compatible with classic and executive faceplate frames





CHD9CIWY

CHD15HDCIWY



	Part Number	Part Description	Color‡	Pkg.	Std. Ctn. Qty.
	CHD9CIWY	1/3 insert with 9-pin female to female coupler.	Off White	1	10
	CHD15HDCIWY	1/3 insert with 15-pin high density female to female coupler; SVGA capable.	Off White	1	10
	CHD15HDSCIWY	1/3 insert with one 15-pin DB connector mounted to a printed circuit board; terminates on site; SVGA capable.	Off White	1	10

‡For other colors, replace suffix IW (Off White) with EI (Electric Ivory), WH (White), IG (International Gray), or BL (Black).

Compatible with Classic and Executive Faceplate Frames on page G.14 of SA-NCCB51.