





PANDUIT PART NUMBER	STRANDED COPPER WIRE RANGE	SCREW TORQUE IN-LB [N.m]	STUD SIZE (IN)	DIMENSIONS - IN [mm] ±.03 [0.8]										SCREW
				D DIA	G	S	W	A	М	Т	Н	L	C (REF)	STYLE
CD\$35-36-Q	14 AWG - 6 AWG	13 IN-LB [1.5 N.m]	3/16"	0.20 [5.0]	0.22 [5.6]	1.00 [25.4]	0.39 [9.9]	2.17 [55.1]	0.47 [11.9]	0.06 [1.5]	0.55 [14.0]	0.36 [9.1]	0.38 [9.6]	5/64'' HEX SOCKET
CD\$70-14-Q	8 AWG - 2 AWG	8 AWG = 20 IN-LB [2.3 N.m] 6 AWG = 23 IN-LB [2.6 N.m] 4-2 AWG = 35 IN-LB [4.0 N.m]	1/4"	0.26 [6.6]	0.25 [6.4]	1.00 [25.4]	0.50 [12.7]	2.29 [58.2]	0.53 [13.5]	0.08 [2.1]	0.65 [16.6]	0.46 [11.6]	0.34 [8.6]	1/8" Hex socket

	1					
		İ				
	Ì					
	Ì					
01	3/21	ЈНМИ	TMR	JADE	CDS70-14-Q RELEASED	098721
00	10/20	JHNU	TMR	ALP	DRAWING RELEASED	089914
REV	DATE	BY	СНК	APR	DESCRIPTION	ECN

NOTES:

1. MATERIAL: BODY - COPPER SCREW - STEEL, ZINC PLATED

2. TWO PIECE FLOATING TONGUE ASSEMBLY.

3. CULUS LISTED FOR USE UP TO 600V AND TEMPERATURE RATED 90 °C

4. RATED FOR USE WITH COPPER STRANDED CODE CONDUCTOR ONLY

5. THESE PARTS ARE ROHS COMPLIANT

6. PKG. QTY.: Q = 25



